Contract No. 153

5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY	Jicarilla Apache
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a differen	7. UNIT AGREEMENT NAME
reservoir, Use Form 9–331–C for such proposals.)	_ 8. FARM OR LEASE NAME 第一直意思 Jicarilla 神力概算 まままま
1. oil gas X other	9. WELL NO. 87.8 1 2 8 7 7
2. NAME OF OPERATOR SUPRON ENERGY CORPORATION	18 TELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	South Blanco Pictured Cliffs
P.O. Box 808, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OF
 LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 	Sec. 36, T-26N, R-5W, N.M.P.N
AT SURFACE: 880 ft./N; 915 ft./E line	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same as above AT TOTAL DEPTH:	Rio Arriba New Mexico
Same as above 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO. 플로플 및 설득 기를 다 기를
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	6664 Gr.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	지 <u>기 기 기 기 기 기 기 기 기 기 기 기 기 기 기 기 기 기 기</u>
FRACTURE TREAT	100 100 100 100 100 100 100 100 100 100
SHOOT OR ACIDIZE	ANOTE: Pared with the second s
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
MULTIPLE COMPLETE	
CHANGE ZONES	그
(other)	
	<u> </u>
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stational including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertined.)	directionally drilled, give subsurface locations and
1. Spudded 9-7/8" hole at 2:00 p.m. 7-11-79	()
1. Spaced 5 7,0 Hole at 1000 pemo 1 11 15	ិននៅក្នុង ខ្លាំង
2. Drilled surface hole to T.D. of 215 ft.	R.K.B.
3. Ran 5 joints of 7-5/8", 20# casing. Lan	ded at 213 ft. R.K.B.
4. Cemented with 150 sacks of class "B" wit	h 2% Calcium Chloride
Cement did not circulate. Cemented top	
"B". Brought cement to surface.	
5. Waited on cement 12 hours.	
6. Pressure-tested casing to 1000 PSIG for	15 minutes Held 90K = First
Subsurface Safety Valve: Manu. and Type	Set @Ft
18. I hereby certify that the foregoing struct and correct	
Roan Al E. Kalaly Production S	upt July 16, 1979 & 3
Kenneth E. Roddy	DATE
(This space for Federal or State o	ffice use) The base of the second sec
APPROVED BY TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:	그는 그는 그는 그는 그를 하는 그들은

*See Instructions on Rev