5. LEASE

Contract No. 105

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

GEOLOGICAL SURVEY	6. IFINDIAN, ALLOTTEE OR TRIBE NAME Jicarilla Apache	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME	
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.) $ \frac{1}{2} \int_{-\infty}^{\infty} \frac{1}{2} \left(\frac{1}{2} \int_{-\infty}^{\infty}$	8. FARM OR LEASE NAME	
1. oil gas g	Jicarilla "A"	
well gas well other	9. WELL NO.	
2. NAME OF OPERATOR	23	
SUPRON ENERGY CORPORATION	10. FIELD OR WILDCAT NAME	
3. ADDRESS OF OPERATOR	Blanco Mesaverde	
P.O. Box 808, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
below.)	Sec. 24, T-26N, R-4W, N.M.P.M.	
AT SURFACE: 1155 ft./S; 1060 ft./E line	12. COUNTY OR PARISH 13. STATE	
AT TOP PROD. INTERVAL: Same as above. AT TOTAL DEPTH: Same as above.	Rio Arriba New Mexico	
	14. API NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	7270 GR.	
TEST WATER SHUT-OFF		
FRACTURE TREAT		
SHOOT OR ACIDIZE	(NOTE: Depart results of multiple completion or response	
REPAIR WELL PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on Form 9-330.)	
MULTIPLE COMPLETE		
CHANGE ZONES		
ABANDON*		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinent	irectionally drilled, give subsurface locations and	
1. Spudded 13-3/4" surface hole at 7:00 p.m.	9-19-79.	
2. Drilled 13-3/4" hole to total depth of 256	5 ft. R.K.B.	
3. Ran 7 joints of 9-5/8", 32.30#, H-40 casir	ng. Landed at 256 ft. R.K.B.	
4. Cemented with 225 sacks of class "B" with 11:45 a.m. 9-20-79. Cement circulated to		
5. Waited on cement 12 hours.		
6. Pressure-tested casing to 1000 PSI for 15	minutes. Held OK.	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.	
18. I hereby certify that the foregoing it true and correct SIGNED Servett E. Kodoy TITLE Production Sup	ot. page 9-21-79	
Kenneth E. Roddy	DATE	
(This space for Federal or State of	te use)	
APPROVED BY TITLE		
SEPS	5 1979	
0/4 00%	SEP 24 1979	