

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
SUPRON ENERGY CORPORATION
3. ADDRESS OF OPERATOR  
P.O. Box 808, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 905 ft./N ; 1520 ft./E line  
AT TOP PROD. INTERVAL: Same as above.  
AT TOTAL DEPTH: Same as above.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) <u>Run and cement casing</u>		

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Drilled 9-7/8" hole with mud to intermediate depth of 3950 ft. R.K.B. Ran 92 joints of 7-5/8", 26.40#, K-55 casing and landed at 3950 ft. R.K.B. Cemented with 100 sacks of Halliburton Lite and 100 sacks of class "B" with 2% Calcium Chloride. Plug down at 9:45 p.m. 10-10-79. Top of cement indicated at 2700 ft. R.K.B.
2. Drilled 6-3/4" hole with air to total depth of 8044 ft. R.K.B. Ran 104 joints (4246 ft.) of 5-1/2", 15.50#, K-55 casing as a liner. Bottom of liner at 7998 ft. R.K.B. Top of liner at 3752 ft. R.K.B. Cemented with 500 sacks of 50-50 POZ mix. Plug down at 5:00 a.m. 10-20-79.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

18. I hereby certify that the foregoing is true and correct

SIGNED Kenneth E. Roddy TITLE Production Supt. DATE APR 23 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

\*See Instructions on Reverse Side

NMOCC

APR 23 1980  
FARMINGTON DISTRICT  
BY M. L. Kuchera