

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER
2. NAME OF OPERATOR
Southland Royalty Company
3. ADDRESS OF OPERATOR
P. O. Drawer 570, Farmington, NM 87401
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1070' FSL & 1840' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7072' GR

5. LEASE DESIGNATION AND SERIAL NO.

Jicarilla 101

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla 101

9. WELL NO.

#8

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde
Blanco Pictured Cliffs11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 12, T26N, R4W

12. COUNTY OR PARISH 13. STATE

Rio Arriba

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Perforation and Stimulation

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-8-79 Perforated the Mesa Verde at 5572', 5581', 5588', 5595', 5602', 5864', 5872', 5898', 5906', 5926', 5934', 5942', 5957', 5965', 5976', 5983', 5990', 6007', 6054', 6062', 6070'. Total of 21 holes.
Brokedown with 1,575 gallons of 15% HCl and balls.
Fracd with 164,000 gallons of water and 159,000# of 20/40 sand.
ATP 1875, AIR 40, ISIP Vac.
Set retrievable bridge plug at 3990'.

9-9-79 Perforated the Pictured Cliffs at: 3796', 3803', 3820', 3829', 3834', 3841'.
Total of 6 holes.
Brokedwon with 450 gallons of 15% HCl.
Fracd with 50,300 gallons of water and 48,300# of 20/40 sand.
ATP 1150, AIR 11, ISIP 300.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE District Production Manager DATE 9-11-79

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

SEP 12 1979

*See Instructions on Reverse Side