STATE OF NEW MEXICO

ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

2002

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator	CORDILLERA ENERGY, INC.			Lease HURON			Well No2E		
Location of Well	Unit <u>M</u>	_ Sec.	2	_ Twp.	_26N	Rge. <u>4W</u>	API #	30-039-22100	
	NAME OF RESERVOIR C	DR POOL	<u>-</u>	1	OF PROD.		METHOD OF PROD.	PROD. MEDIUM	
Upper				(Oil or	Gas)		(Flow or Art. Lift)	(Tbg. or Csg.)	
Completion Lower	GALLUP			GAS			FLOW	TBG	
Completion	DAKOTA			GAS			FLOW	TBG	
			PRI	E-FLOW SHU	T-IN PRF	SSURE D	ΔΤΔ		
Upper	Hour, date shut-in			Length of time shut-in			ss. psig	Stabilized? (Yes or No)	
Completion	10/11/02			3 days	;		158	ves	
Lower	Hour, date shut-in			Length of time shut-in		Si pre	ss. psig	Stabilized? (Yes or No)	
Completion	10/11/02			3 days			291	yes	
				FL	OW TEST	NO. 1			
Commenced	at (hour, date) *	10/14/02			Zone produ	ucing (Upper	or Lower):	Lower	
TIME	LAPSED TIME		PRESSURE		PROD. ZONE	<u> </u>		201101	
(hour, date)	Since *	Upper Complet		Lower Completion	TEMP.		REMARK	S	
		csg	tbg	tbg					
10/12		145	142	210]	Botl	n Zones Shut In		
10/13		153	150	255					
10/13		133	150	255		Boti	n Zones Shut In		
10/14		163	158	291		Botl	n Zones Shut In		
10/15	1 day	176	170	51		Low	er Zone Flowing		
		1		01		LOW	el Zolle Flowling	-	
10/16	2 days	214	170	48		Low	er Zone Flowing		
Production	rate during test								
<u> </u>	BOPD ba	ased on		Bbls. in		Hours	Grav.	GOR	
Gas:		167		MCFPD: Tested	thru (Orifice	or Meter):	METER		
 -			MID-	TEST SHUT-I	N PRESS	URE DATA	A		
Jpper Completion	Hour, date shut-in			Length of time shut-in			ss. psig	Stabilized? (Yes or No)	
ower	Hour, date shut-in			Length of time shut-in			ss. psig	Stabilized? (Yes or No)	
ompletion									

NORTHWEST NEW MEXICO PACKER-LEAKAGE

FLOW TEST NO. 2

Commenced	at (hour, date) **		Zone F	Zone Producing (Upper or Lower):				
Time LAPSED TIME			PRESSURE					
(hour, date)	SINCE **	Upper Completion	Lower Compl	etion T	EMP.	REMARKS		
<u> </u>								
	 							
L					 			
Productio	n rate during test	Į.						
Oil:	BOPD	based on	Bbls. in	Hrs.		_GravGOR		
Gas:		MCFPD: Tested	thru (Orifice or Meter):					
								
Remarks:	·							
I hereby cer	tify that the information	n herein contained is to	ie and complete to the	best of my kno	owledge.			
	Nilv 1	4 2002	0000	Onerster	COBDII	LERA ENERGY, INCORPORATED		
Approved	" 		, 2002	Operator	7/	OV A		
New Mex	cico Oil Conserva	ition Division			Variable			
4,54	· Maria Marian W	GHAST PLANS	1	By	Cayre	epseur		
Ву				Title	PRODU	CTION TECHNICIAN		
	MALL STATE	IMPICITIA, Dei g	,	Date	11/12/02	2		
i iuc								

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distrubed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak 'was indicated during Flow
 Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a dead-weight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-nminute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests; immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)