

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Tribal "C" 1052

9. WELL NO.

10-E

10. FIELD AND POOL, OR WHDCAT

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

sec 7, T26, R3

12. COUNTY OR PARISH

Rio Arriba

13. STATE

NM

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Consolidated Oil & Gas, Inc.

3. ADDRESS OF OPERATOR

1860 Lincoln St., Suite 1300, Denver, CO. 80295

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

850' FNL & 1665' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7238' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)


17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-23-79 Drill 296' of 14-3/4" surface hole. Run 292' 10-3/4" surface pipe & cement with 200 sks. class "B" neat.

9-28-79 Drill 9-7/8" hole to 4300' KB

9-29-79 Ran 102 jts. (4286') 7-5/8" K-55 26.4# LTC casing. Cement w/150 sks. 65/35 poz mix 12% 1/4# Celloflake and 100 sks. class "B" neat 2% CC 1/4# celloflake per sk. Plug down 2:15 a.m. 9-29-79

10-3-79 Drill 6-3/4" to 8400' KB with air. Ran 112 jts. 5 1/2" K-55 casing to 8399'. Top of liner 4139'. BJ cemented w/350 sks 50/50 poz 4% gel 10# fine gilsonite & 0.6% FLA. Plug down 6:30 a.m.



18. I hereby certify that the foregoing is true and correct

SIGNED

Veryl Moore

TITLE

Prod. Supt.

DATE

10-12-79

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
OCT 15 1979U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

*See Instructions on Reverse Side