

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, NM

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
1530'S, 1450'W
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☒
☐
☐
☐
☐
☐
☐

5. LEASE
SF 079266

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Vaughn

9. WELL NO.
32

10. FIELD OR WILDCAT NAME
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 29, T-26-N, R-6-W
NMPM

12. COUNTY OR PARISH
Rio Arriba

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6462' GL

(NOTE: Report results of multiple completions or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS* (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 11-24-80: Perf'd two squeeze holes at 7274', and one at 7273'. Perf'd one hole at 6916'. Set cement retainer at 7264'. Pressure tested tubing to 3500# held ok. Cemented w/ 118 cu. ft. cement.
- 11-26-80: Set 4 1/2", RTTS at 6898'. Top squeeze hole at 6884'. Pressure tested to 4000#, Held ok. Set cement retainer at 6804'. Cemented w/ 59 cu. ft. cement.
- 11-29-80: PBTD 7279'. Tested casing to 4000#, OK. Perf'd 6916, 6922, 6928, 6967, 6972, 6078, 7010, 7016, 7033, 7045, 7056, 7078, 7082, 7125, 7131, 7137' W/1 SPZ. Fraced w/ 210,000# 20/40 sand, & 40,500# 10/20 sand, 181,200 gal. wtr. Flushed w/4400 gal. wtr.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED D. J. Guice TITLE Drilling Clerk DATE Dec. 4, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NMOCC

*See Instructions on Reverse Side