STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting pacter leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

tor <u>Ene</u>		2/1/	Lease	Tic 150 1 5W	County	No. 14 Scio Acriba	
NAME OF RESERVOIR OR POOL			TYPE OF P	NOO.	METHOD OF PROD. (Flow or Art. LHI)	PROD, MEDIUM (Tbg. or Cog.)	
or P.C. :			6113	F	 10:22 :	Tha.	
			6115	<u> </u>	1/1 1/11	Tog-	
				RESSURE DATA	A [Sta	bilized? (Yes or No)	
Hour, date shut-in Length of time shu Hour, date shut-in		The 311		√ Sta	bilized? (Yes or No)		
etion $\prod_{i=1}^{n} f_{i,i}^{i} f_{i,i}^{i}$	P1 321 72		FLOW TEST		,		
enced at (hour, date) *				Zone producing (Upper or Lowerk		
TIME (hour, date)	LAPSED TIME	Upper Completion	Lower Completion	PROD. ZONE TEMP.		REMARKS	
0119-0199	92 118 2	370/359	15		PROD P.	C. Time Uffer	
1. 1.02.49_	101 His	170/500	150			· ·	
111.	143 : 48:	16/80	K.				
			 		US OCT	- 5 1999	
						ON. DIV.	
		PD based onMO	Bbls.	in Ho	_	න්න ව av GOR	
s:		MID-	TEST SHUT-IN	PRESSURE DA	TA	Stabilized? (Yee or No)	
Upper Hour, date shut-in Length of time moletion Length of time			Si press. pelg		Stabilized? (Yes or No)		

FLOW TEST NO. 2

				Zone producing (Upper or Lower)		
This E Shows, date)	LAPSED TIME SINCE **	PRESSURE				
		Upper Completion	Lower Completion	PROD. ZONE TEMP.	REMARKS	
			1			
		· · · · · · · · · · · · · · · · · · ·				
Production rate di	uring test					
Gas:		MCFF	PD: Tested thru ((Orifice or Meter)	Grav GOR	
hereby certify the	ot the information of 5	n herein containe 1999	d is true and con	aplete to the best	of my knowledge.	
Approved			- 19 Or	erator <u>Enc.</u>	gen Passinces	
ORIGINAL SIGNED BY CHARLE			Ву	- PARC	Lunan	
PEPUTY OIL & GAS INSPECTOR, DIST. #8				le	Courtain	
				te <u> </u>		
				. 		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the rubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Commonand at thour, date! # #

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone term must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours term: immediately prior to the beginning of each flow-period, at fafteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day term: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).