

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

5. Lease Designation and Serial No.

Jicarilla Contract 109

6. If Indian, Allottee or Tribe Name

Jicarilla, Dulce N.M.

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Jicarilla B

8M

9. API Well No.

3003922300

10. Field and Pool, or Exploratory Area

Blanco Mesaverde/Basin Dakota

11. County or Parish, State

Rio Arriba

New Mexico

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Amoco Production Company

Attention:

Patty Haefele

3. Address and Telephone No.

P.O. Box 800, Denver, CO 80201

(303) 830-4988

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1020' FNL

1685' FWL

Sec. 15 T 26N R 5W

Unit C

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Downhole Commingle

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Amoco Production Company requests permission to mill up the packer and downhole commingle this well per the attached procedure. (DHC approval by NMOCD is pending.)

RECEIVED
MAR 20 1996
OIL CON. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed

Patty Haefele

Title

Staff Assistant

Date

03-12-1996

(This space for Federal or State office use)

Approved by

Robert Kent

Title

for Chief, Lands and Mineral Resources

Date

MAR 19 1996

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instructions on Reverse Side

SJOET Well Work Procedure

Wellname: JICARILLA B 8M
Version: 1
Date: 12-Mar-96
Budget: Repair Well Expense
Repair Type: Mill Up Packer

Objectives: Increase gas production by milling up the packer that is set between the Mesaverde and Dakota formations at 7350', cleaning out the wellbore to PBTD of 7624', downhole commingling the production streams and returning the well to production with 2-3/8" tubing landed at 7604'.

Pertinent Information:

Location:	C15 26N 05W, 1020 FNL 1685 FWL	FM:	MV, DK
County:	Rio Arriba	API:	3003922300
State:	New Mexico	Engr:	Steve Smethie
Lease:	Indian	Phone:	H--(303)770-2180
Well FLAC:	979316		W--(303)830-5892

TD: 7670 PBTD: 7624

Economic Information:

APC WI:	75 %	Prod. Before Work:	100 MCFD
Estimated Cost:	\$35,000	Anticipated Prod.:	250 MCFD
Payout:	9 Mo		
Max Cost-12 Mo. P.O.:	\$47,000		
PV 15:	\$M		
Max Cost PV 15:	\$M		

Note: Economics will be run on all projects that have a payout exceeding ONE year.

Formation Tops:

Nacimiento:		Mencfee:	4973
Ojo Alamo:		Pt Lookout:	5486
Kirtland Shale:		Mancos Shale:	5566
Fruitland:		Gallup:	6999
Pictured		Graneros:	
Lewis Shale:		Dakota:	7396
Cliff House:	4894	Morrison:	

Bradenhead Test Information:

Test Date: 6/2/95 Tubing: 320 Casing: 540 BH: 0

Time	BH	CSG	INT	CSG
5 min:	0	540		
10 min:	0	540		
15 min:	0	540		

Comments:

Suggested Procedure

1. Pull and lay down the 2-3/8" tubing that is landed at 5100' on the Mesaverde side.
2. Unseat the seal assembly that is set in the Baker Model "F-1", size 24-23 4-1/2" Retainer Production Packer at 7345'. Pull the 2-3/8" tubing that is landed at 7350' on the Dakota side.
3. Mill up and pluck the Baker Model "F-1", size 24-23 4-1/2" Retainer Production Packer that is set at 7345' in 4-1/2", 10.5 #/Ft, K-55 casing. Utilize the air package with the booster compressor.
4. Clean out the wellbore to PBTD OF 7624' by running a bit and scraper. Sweep the wellbore clean.
5. Trip in the hole with a Mule Shoe, Seating Nipple, and 2-3/8" tubing. Land the tubing at 7604'.
6. Broach the tubing to be sure there are no tight spots. We may want to run a plunger in this wellbore at a later date.
7. Swab the well in if necessary and notify the pumper that the well has been returned to production.

BLM CONDITIONS OF APPROVAL

Operator Amoco Production Company Well Name Jic B 8M

Legal Location 1020 FNL, 1685 FWL Sec. 15 T. 26 N. R. 5 W.

Lease Number Jic Cont. 109

The following stipulations will apply to this well unless a particular Surface Managing Agency (SMA) or private surface owner has supplied to BLM and the operator a contradictory environmental stipulation. The failure of the operator to comply with these requirements may result in the assessments or penalties pursuant to 43 CFR 3163.1 or 3163.2. A copy of these conditions of approval shall be present on the location during construction, drilling and reclamation activity.

An agreement between operator and fee land owner will take precedence over BLM surface stipulations unless (In reference to 43 CFR Part 3160) 1) BLM determines that operator's actions will affect adjacent Federal or Indian surface, or 2) operator does not maintain well area and lease premises in a workmanlike manner with due regard for safety, conservation and appearance, or 3) no such agreement exists, or 4) in the event of well abandonment, minimum Federal restoration requirements will be required.

1. Pits will be fenced during workover operation.
2. All disturbances will be kept on existing pad.
3. Remove all hydrocarbons from temporary pit prior to closure.
4. Workover fluids will be contained in a lined pit or frac tank.