

Operator Caulkins Oil Company Lease Breech "E" Well No. 54-E
Location _____
of Well: Unit P Sec. 4 Twp. 26 North Rge. 6 West County Rio Arriba

PRE-FLOW SHUT-IN PRESSURE DATA				
Upper	Hour, date	Length of	SI press.	Stabilized?
Compl	Shut-in	time shut-in	osig	(Yes or No)
Lower	Hour, date	Length of	SI press.	Stabilized?
Compl	Shut-in	time shut-in	osig	(Yes or No)

Commenced at (hour, date)*		8:00 AM 5-12-84		Zone producing (Upper or Lower):	
Time (hour, date)	Lapsed time since*	Pressure		Prod. Zone Temp.	Remarks
		Upper Compl.	Lower Compl.		
5-13-84	24 Hours	497	599		Both Zones Shut-in
5-14-84	48 Hours	507	683		Both Zones Shut-in
5-15-84	72 Hours	517	690		Both Zones Shut-in
5-16-84	96 Hours	517	438		Dakota Flowing Mesa Verde SI
5-17-84	120 Hours	517	436		Dakota Flowing Mesa Verde SI

Oil: _____ BOPD based on _____ Bbls. in _____ Hrs. _____ Grav. _____ GOR _____
Gas: _____ MCFPD; Tested thru (Orifice or Meter): _____

Upper	Hour, date	Length of	SI press.	Stabilized?
Compl	Shut-in	time shut-in	psig	(Yes or No)
Lower	Hour, date	Length of	SI press.	Stabilized?
Compl	Shut-in	time shut-in	psig	(Yes or No)

[illegible]

Oil: _____ BOPD based on _____ Bbls. in _____ Hrs. _____ Grav. _____ GOR _____
Gas: _____ MCFPD; Tested thru (Orifice or Meter): _____

hereby certify that the information herein contained is true and complete to the best of my knowledge.

Original Signed by, CHARLES JOHNSON

Date 5-24-84

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as mandated by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or sealant has been disturbed. Tests shall also be taken at any time the Administration is requested or when requested by the Division.

2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be conducted. Licensed operators shall also be so notified.

3. The above leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.

4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 14 days in the case of an oil well. NOTE: If, on an initial packer leakage test, a well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in until the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at the intervals as follows: 3-hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period at approximately the midway point, and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

14-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges, the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Area District Office of the Oil Conservation Division in Northwest New Mexico Packer Leakage Test Form Revised 10-1-53, (with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and API (oil zones only)). A pressure versus time curve for each zone of each test shall be constructed on the reverse side of the Packer Leakage Test Form with all deadweight pressure points taken indicated thereon. For oil zones, the pressure curve should also indicate all key pressure changes which may be reflected by the recording gauge charts. These key pressure changes should also be tabulated on the front of the Packer Leakage Test Form.

