

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR  
Tenneco Oil Company

3. ADDRESS OF OPERATOR  
P. O. Box 3249, Englewood, CO 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1750' FSL 1000' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☒  
☐  
☐  
☐  
☐

5. LEASE  
SF 080658

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Reames Com

9. WELL NO.  
1E

10. FIELD OR WILDCAT NAME  
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 25, T26N, R6W

12. COUNTY OR PARISH  
Rio Arriba

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6614' gr.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*  
9/26/80

MIRUSU. NDWH. NUBOP. Drilled DV tool @ 4411' PT. csg to 1600 PSI. TOH w/tbg. TIH w/4 1/2" fullbore pkr on 2 3/8" tbg. Isolated csg. leak @ DV tool 4411'. Set pkr @ 3751'. Rate @ 2 BPM @ 1700 PSI into formation. P Press'd annulus to 1000 PSI. Cmt'd down tbg. w/50 sx CL-B cmt. Released pkr & TOH w/ tbg & pkr. TIH w/bit, csg. scraper & 2 3/8" tbg. Tagged cmt. @ 3779. Drilled 3621' cmt. PT squeeze on DV tool to 3500 PSI. Held 5 mins. TIH w/2 3/8" tbg. Tagged cmt. @ 7200. Drill 75' cmt. to 7275'. PT csg. to 3500 PSI. Circ'd hole w/1% KCL water.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Carley Matheson TITLE Asst. Div. Adm. Mgr. DATE 10/18/80

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

OCT 26 1980

NMOC

\*See Instructions on Reverse Side

BY

BW  
FARMINGTON DISTRICT