

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Supron Energy Corporation

3. ADDRESS OF OPERATOR
P.O. Box 808, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 800 Ft./N; 800 Ft./E line
AT TOP PROD. INTERVAL: Same as above
AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Spudded 12-1/4" hole at 8:00 P.M. 9/27/80.
2. Drilled 12-1/4" surface hole to total depth of 262 ft. R.K.B.
3. Ran 6 joints of 8-5/8", 24.00#, H-40 casing and landed at 262 ft. R.K.B.
4. Cemented with 200 sacks of class "B" with 2% calcium chloride and 1/4 lb. flocele per sack. Cement circulated to surface.
5. Waited on cement for 12 hours.
6. Pressure - tested casing to 600 P.S.I. Held ok.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kenneth E. Roddy TITLE Production Supt. DATE October 7, 1980
Kenneth E. Roddy

(This space for Federal or State office use)

APPROVED BY ENTERED FOR RECORD
CONDITIONS OF APPROVAL IF ANY

TITLE _____ DATE _____

OCT 09 1980

NMOCC

BY BW FARMINGTON DISTRICT

*See Instructions on Reverse Side