STATE OF NEW MEXICO SENERGY and MINERALS DEPARTMENT OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests

perator Men	idian O	1 200	Lease _	Ticari	114 J	Wei No.	IDE	
					5W		a Arriba	
Upper per per la completion De Reservoir de Pool Lower per per la completion De Rock (1988)			TYPE OF I	PROD.	METHOD OF PROD. (Flow or Art. Lift)		PROD. MEDIUM (Tog. or Cag.)	
			Coci					
			(200		Flori	/	The	
		PRE-FL	OW SHUT-IN F		DATA	······································	7	
Hour, date shul-in Length of time shul-in			uliin Musik	SI press. psig		Stabilized? (Yes or No)		
Lower		Length of time en	· /	SI press. psi			Stabilized? (Yes or No)	
npietion 1-5	-7.5	1 50	AYS		<u>82n</u>			
menced at (hour, date)	* VI~10-6	}	FLOW TEST		iducing (Upper or Lowe	a hour	: A	
TIME LAPSED TIME		PRE	PRESSURE		ZONE	REMARKS		
hour, date)	SINCE*	Upper Completion	Lower Completion	TEI	IP.		 	
1.8-93		<u> </u>	500			-		
11-9-93		320	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\				·····	
1-12-93		326	820					
11-11-63		302	290			- <u>**</u>	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
11-1293		318	306					
oduction rate du	ring test							
l: BOPD based on			Bbls. i	3bls. in Hours		Grav GOR		
ıs:		MC	FPD; Tested thr	u (Orifice	or Meter):			
		MID-T	EST SHUT-IN F	RESSURE	DATA			
Upper Hour, date shi	Hour, date shut-in Length of time shut-in		nut-in	SI press. psig		Stabilized? (Yes or No)		
Hour, date shut-in Ler		Length of time ar	ength of time shut-in		SI press. psig		Stabilized? (Yes or No)	
mpietion		1	···					
						- N	555 CT . T	

OIL MAN

			FLOW TEST I	NO. 2				
Commenced at (hour, de	1(e) + +			Zone producing (Upper or Lower):				
TIME (hour, date)	LAPSED TIME	PRESSURE		PROD. ZONE	DEMARYS			
	SINCE **	Upper Completion	Lower Completion	TEMP.	REMARKS			
	!							
			1					
			-					
			1	!				
	3OF				Grav GOR			
Remarks:								
				•	t of my knowledge.			
Approved			19 (Decaror Me	endian Oil Inc			
	Oil Conservation							
			E	Зу	SUSAN DOLAN ERATIONS ASSISTANT			
Original Signed by CHARLES SHOLSOM				OPE	ERATIONS ASSISTANT			
· · · · · · · · · · · · · · · · · · ·			· · · · · · · · · · · · · · · · · · ·	Tide				
Title DEPUTY OIL & GAS INSPECTOR, DIST. #				Date	W			

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6 Flow Test No. 2 shall be conducted even though no leak was indicated during Flow LEST NO. 1. I POCCEDURE FOR FIOW LEST ING. 2 at to be the same as for Fiow Lest ING. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previous-
- ly shut-in is produced. 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginn-

ing of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing , temperatures (gas zones only) and gravity and GOR (oil zones only).