

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other
2. NAME OF OPERATOR  
Supron Energy Corporation
3. ADDRESS OF OPERATOR  
P.O. Box 808, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1005 Ft./S; 940 Ft./E line  
AT TOP PROD. INTERVAL: Same as above  
AT TOTAL DEPTH: Same as above
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA


REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other)

SUBSEQUENT REPORT OF:

☒ RECEIVED  
NOV 30 1980  
U.S. GEOLOGICAL SURVEY  
FARMINGTON, N.M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



5. LEASE  
Contract No. 153
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Jicarilla Apache
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Jicarilla "J"
9. WELL NO.  
20
10. FIELD OR WILDCAT NAME  
South Blanco Pictured Cliffs
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 26, T-26N, R-5W, N.M.P.M.
12. COUNTY OR PARISH  
Rio Arriba
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6645 R.K.B.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- Spudded 12-1/4" surface hole at 10:15 P.M. 10/30/80.
- Drilled 12-1/4" surface hole to total depth of 262 ft. R.K.B.
- Ran 6 joints of 7-5/8", 26.40#, K-55 casing and set at 262 ft. R.K.B.
- Cemented with 220 sacks of class "B" with 2% calcium chloride. Plug down at 7:45 A.M. 10/31/80. Cement circulated to surface.
- Waited on cement for 12 hours.
- Pressure - tested casing to 1000 P.S.I. for 15 minutes. Held ok.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kenneth E. Roddy TITLE Production Supt. DATE November 3, 1980  
Kenneth E. Roddy

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

MAJCCG

\*See Instructions on Reverse Side

BW