

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR  
**Supron Energy Corporation**

3. ADDRESS OF OPERATOR  
**P.O. Box 808, Farmington, New Mexico 87401**

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: **800 Ft./South; 980 Ft./West line**  
AT TOP PROD. INTERVAL: **Same as above**  
AT TOTAL DEPTH: **Same as above**

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE

**Contract No. 153**

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
**Jicarilla "J"**

9. WELL NO.

**12-E**

10. FIELD OR WILDCAT NAME

**Basin Dakota**

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
**Sec. 35, T-26N, R-5W N.M.P.M.**

12. COUNTY OR PARISH  
**Rio Arriba**

13. STATE  
**New Mexico**

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
**6654 GR**

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

AUG 5 1980

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Spudded 12-1/4" surface hole at 5:30 A.M. 8-15-80.
2. Drilled 12-1/4" hole to total depth of 288 ft. R.K.B.
3. Ran 6 joints of 8-5/8", 24.00 lb., K-55 casing. Landed at 283 ft. R.K.B.
4. Cemented with 200 sacks of class "B" with 2% Calcium Chloride. Plug down at 2:15 P.M. 8-5-80. Cement circulated to surface.
5. Waited on cement for 12 hours.
6. Pressure - tested casing to 600 P.S.I. for 15 minutes. Held OK.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kenneth E. Roddy TITLE Production Supt. DATE August 6, 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
ACCEPTED FOR RECORD IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

AUG 12 1980

\*See Instructions on Reverse Side

FARMINGTON DISTRICT  
BY RW

NMOCC

[illegible]