

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well  
2. NAME OF OPERATOR  
Amoco Production Company  
3. ADDRESS OF OPERATOR  
501 Airport Drive, Farmington, NM 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1110' FSL x 1065' FWL  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Completion ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED

JAN 2 1981

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE  
Jicarilla Apache 102  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Jicarilla Apache  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Jicarilla Apache 102  
9. WELL NO.  
11E  
10. FIELD OR WILDCAT NAME  
Basin Dakota  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
SW/4, SW/4, Section 10, T26N, R4W  
12. COUNTY OR PARISH  
Rio Arriba NM  
13. STATE  
14. API NO.  
30-039-22459  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6839' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Completion operations began on 10-30-80. Drilled cement to PBD of 7935. Pressure tested casing to 3800 PSI, held ok. Perforated 7896-7902 x 4 spf of .38 inch diameter, total of 24 holes. Perforated 7710-7762 and 7852-7873 x 2 spf of .38 inch diameter, total of 156 holes. Fraced with 132,000 gal fluid and 444,000 lbs. sand. Circulated sand out with nitrogen. Landed 2 3/8" tubing at 7914'. Swabbed. Completion rig released 11-5-80.

Subsurface Safety Valve: Manu. and Type

Set @ JAN 8 1981 Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Admin. Supvr.

DATE 12-30-80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF AREA ACCEPTED FOR RECORD

JAN 07 1981

FARMINGTON DISTRICT

\*See Instructions on Reverse Side

AMCCG