

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR

AMOCO PRODUCTION COMPANY

3. ADDRESS OF OPERATOR

501 Airport Drive, Farmington, NM

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

1080' FSL x 1570' FEL

AT SURFACE:

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA


REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐


(other) Completion

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐



(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Completion operations commenced on 1-31-81. Total depth of the well is 5355' and plugback depth is 5325'. Perforated intervals from 5064-5070', 5100-5139', 5182-5186', 5207-5212', 5227-5231', and 5262-5270' with 2 spf, a total of 132, .4" holes. Sand water fraced mesaverde with 60,000 gallons of frac fluid and 102,000# of 10-20 sand. Perforated intervals from 4974-4982', 4990-4996', and 5005-5012' with 2 spf, a total of 42, .4" holes. Squeezed the perforations with 100 sx of Class "B" Neat cement. Perforated chacra intervals from 3882-3888 with 4 spf, a total of 24, .38" holes. Fraced Chacra with 20,000 gallons of foam and 33,000# of 10-20 sand. Perforated intervals from 3781-3813' with 2 spf, a total of 64, .38" holes. Fraced chacra with 58,000 gallons of foam and 93,500 # of 10-20 sand. Landed 2 1/16" mesaverde tubing at 5245' and 1 1/4" chacra tubing at 3890'. Swabbed the well and released the rig on 2-23-81.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED **L. L. SVOLODA**

TITLE Dist. Admin. Supvr. DATE 2/25/81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NMOCO

RECEIVED

MAR 4 1981

FARMINGTON DISTRICT