

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

501 Airport Drive, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 840' FSL x 1800' FWL

AT TOP PROD. INTERVAL: same

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other) Completion

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
FEB 06 1981
GEOLOGICAL SURVEY
WASHINGTON, D.C.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE

Jicarilla Apache "A" No. 118

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jicarilla Apache "A" No. 118

9. WELL NO.

6

10. FIELD OR WILDCAT NAME *Taxaco*

Pictured Cliffs/Blanco Mesaverde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SE/4, SW/4, Section 35

T26N, R3W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

NM

14. API NO.

30-039-22508

15. ELEVATIONS (SHOW DF, KDB, AND WD)

7388' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Completion operations commenced on 1-9-81. Total depth of the well is 6312' and plug back depth is 6268. Perforated Mesaverde interval from 6162-6177, 6136-6147, 6122-6132, 6106-6118, and 6086-6100, with 2 spf, a total of 124, .38" holes. Sand water fraced Mesaverde with 55,000 gallons of frac fluid and 100,000# 10-20 sand. Perforated Mesaverde intervals from 5652-5658, 5931-5968, 5880-5884, 5843-5864, 5832-5838, 5823-5827, 5809-5814, 5713-5742, 5686-5687, 5671-5676, 5664-5668, with 2 spf, a total of 244, .38" holes. Sand water fraced Mesaverde with 110,000 gallons of frac fluid and 200,000# 10-20 sand. Perforated pictured cliffs intervals from 4000-4011 and 3951-3960 with 2 spf, a total of 40, .38" holes. Sand water fraced pictured cliffs with 100,000 gallons of frac fluid and 180,000# of 10-20 sand. Landed the 2 3/8" Mesaverde tubing at 6184' and the 2 1/16" Pictured Cliffs tubing at 4030'. Swabbed the well and released the rig at 0800 hours on 1-21-81. Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED E. E. SVOBODA TITLE Dist. Admin. Supvr DATE 2-5-81

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY: