Completion

OIL CONSERVATION DIVISION

2001

NORTHWEST NEW MEXICO PACKER-LEAKAGE

Operator	GREYSTONE ENERGY, INC.			Lease NORTHWEST Well No. 3E					
Location of Well	Unit <u>L</u>	Sec.	2	. Twp.	26N	Rge.	War with	30-039-22509	
	NAME OF RESERVOIR OR POOL			TYPE OF PROD. (Oil or Gas)			METHOD OF PROD. (Flow or Art. Lift)	PROD. MEDIUM (Tbg. or Csg.)	
Upper Completion Lower	GALLUP			GA S			FLOW	TBG	
Completion	DAKOTA	GAS			FLOW	TBG			
			PRE	-FLOW SHUT-IN	I PRESSU	JRE D			
Jpper	Hour, date shut-in			Length of time shut-in			SI press. psig	Stabilized? (Yes or No)	
Completion	05/17/01			4 DAYS			336	YES	
Lower Completion	Hour, date shut-in 05/17/01			Length of time shut-in 4 DAYS			SI press. psig 602	Stabilized? (Yes or No) YES	
				FLOV	V TEST N	0.1			
Commenced	at (hour, date) *	05/21/01		Zone producing (U			Jpper or Lower):	LOWER	
TIME	LAPSED TIME		PRESSURE		PROD. ZONE			· · · · · · · · · · · · · · · · · · ·	
nour, date)	Since *	Upper Completio		Lower Completion	TEMP.		REMARK	S	
05/19/01		csg 288	tbg 284	tbg 561			Both Zones Shut In		
05/20/01		321	318	592			Both Zones Shut In		
05/21/01		340	336	602			Both Zones Shut In		
05/22/01	1 DAY	355	354	67			Lower Zone Flowing		
05/23/01	2 DAYS	365	364	64			Lower Zone Flowing		
Production	rate during test BOPD bas	sed on		Bbls. in		Hours	Grav.	GOR	
Gas:		50		MCFPD: Tested thru (Orifice or Meter):			METER		
	¥	-	MID-T	FST SHIIT-IN P	RESSUE	F DAT			
Upper Completion	Hour, date shut-in	EST SHUT-IN PRESSURE DAT			SI press, psig	Stabilized? (Yes or No)			
OWB	Hour date shut-in			Length of time shut in			01		

(Continue on reverse side)

FLOW TEST NO. 2

	at (hour, date) **			Zone Producing (Upper or Lower):			
Time	LAPSED TIME	PRES	SURE	PROD. ZONE			
(hour, date)	SINCE **	Upper Completion	Lower Completion	TEMP.	REMARKS		
			<u> </u>	 			
	.			1			
Production	rate during test						
Oil:	BOPD	pased on	Bbls. in	Hrs.	Grav GOR		
Gas:							
			ira (Omnoc di Mictor).				
Remarks:		· · · · · · · · · · · · · · · · · · ·					
					•		
I hereby certi	fy that the information	n herein contained is tr	ue and complete to ti	he best of my know	rledge.		
	MAVa	0.000	_				
			Opera	ator <u>GREYST</u>	ONE ENERGY, INC.		
New Mexic	co Oil Conservati	on Division			1611 F.		
•	PRIORIAL STONISO	BY CHAPLE T. PSAR	By By	ayo	Cepilein		
Ву		ा विश्व कर स्व	Title	PRODUC	CTION TECHNICIAN		
Title	DEPUTY OF 4 G	AS INSPECTOR DIST.	Date	05/24/01			

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on alt multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distrubed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak 'was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in white the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a dead-weight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-nminute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)