5. LEASE

Contract No. 150

UNITED STATES DEPARTMENT OF THE INTERIOR

DEPARTMENT OF THE INTERIOR	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
GEOLOGICAL SORVET	Jicarilla Apache
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
eservoir. Use Form 9–331–C for such proposals.)	Jicarilla "G"
1. oil gas 🛣 other	9. WELL NO.
2. NAME OF OPERATOR	4E 10. FIELD OR WILDCAT NAME
Supron Energy Corporation	
3. ADDRESS OF OPERATOR	Basin Dakota 11. SEC., T., R., M., OR BLK. AND SURVEY OR
P.O. Box 808, Farmington, New Mexico 87401	AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	Sec. 11, T-26N, R-5W, N.M.P.M.
below.) AT SURFACE: 1800 Ft./N; 630 Ft./W line	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same as above	Rio Arriba New Mexico
AT TOTAL DEPTH: Same as above	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF; KDB, AND WD) 7267 R.K.B.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHIT-OFF	
FRACTURE TREAT	VED
SHOOT OR ACIDIZE	(NOTE: Report results of multiple completion or zone
REPAIR WELL OCT 30	1980 change on Form 9#330.)
MULTIPLE COMPLETE	
CHANGE ZONES U. S. GEOLOGICA	AL SURVEY
ABANDON*	3
	u the and details, and give pertinent dates.
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertine	directionally drilled, give subsurface locations and nt to this work.)*
1. Drilled 6-1/4" hole with gas to total depth total depth on 10/24/80.	of 8340 ft. R.K.B. Reached
2. Ran 118 joints of 4-1/2", 11.6# & 10.5#, K-of liner at 8334 ft. R.K.B. Top of liner at 8318 ft. R.K.B.	-55 casing as a liner. Bottom at 4012 ft. R.K.B. Float collar
3. Cemented liner with 550 sacks of 50-50 poz 1:30 P.M. 10/25/80. Reversed out 5 bbl. ce	with 2% gel. Plug down at ement from liner top.
Subsurface Safety Valve: Manu. and Type	Set @ Ft
18. I hereby certify that the foregoing is true and correct SIGNED SIGNED TITLE Production S	upt. DATE October 27, 1980
(This space for Federal or State of	
APPROVED BY TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:	
	• • •

*See Instructions on Reverse Side

