84

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

| - | oco Produc | tion Co. | Lease | Jicarilla | Contract155 | Well 27 | |
|----------------------------------|-----------------------|----------------------|-------------------------------|--|--|--|--|
| Location of Well: Unit _ | J Sec. 32 | _Twp26 | Rge | 5 | | Rio Arriba | |
| NAME OF RESERVOIR OR POOL | | | TYPE OF | PROD. | METHOD OF PROD. (Flow or Art. Lift) | PROD. MEDIUM (Tbg. or Csg.) | |
| Upper Completion Chacra | | | ga | as f | low | tbg | |
| Completion Mesquerde | | | gā | as f | low | tbg | |
| | | | | PRESSURE DAT | A | | |
| Upper | te shut-in | Length of time sh | | SI press. psig Stabilized? (Yes or No) | | | |
| | | 5 days | | 457 | | yes | |
| completion 2-3-85 | | | Length of time shut-in 3 days | | | ed? (Yes or No) Yes | |
| ommenced at (hour, | 4 | 0.5 | FLOW TEST | NO. 1 | | | |
| | | | | Zone producing (Upper or Lower): Lower | | | |
| TIME (hour, date) | LAPSED TIME SINCE* | Upper Completion | SURE Lower Completion | PROD. ZONE TEMP. | REMARKS | | |
| 2-3-85 | 0 | 310 | 312 | | Both zones shut-in | | |
| 2-4-85 | 1 day | 420 | 407 | | Both zones shut-in | | |
| 2-5-85 | 2 days | 450 | 449 | | Both zones shut-in | | |
| 2-6-85 | 3 days | 457 | 456 | | Both zones shut-in | | |
| 2-7-85 | 4 days | 457 | 332 | | Lower zone flow | | |
| 2-8-85 | 4 days | 457 | 327 | | Lower zone | flow | |
| oduction rate o | | | • | | | | |
| : | BOPI | D based on | Bbls. in | ——— Hours | s Grav | GOR | |
| s: | | MCFP | D; Tested thru | (Orifice or Mete | r): | | |
| | | | | ESSURE DATA | | | |
| pper Hour, date shut-in spletion | | Length of time shut- | in | SI press. psig | Stabilized | Stabilized? (Yes or No) | |
| Hour, date shut-in pletion | | Length of time shut- | Length of time shut-in | | Stabilized | SHOULD ON OUR OF THE STATE OF T | |
| | | | | | | *** E U | |

MAR 06 198**5**

OIL CON. DIV.

FLOW TEST NO. 2

| Commenced at (hour, da | nte) 本本 | f · · · · · · · · · · | Zone producing (Upper or | Lower): | |
|---------------------------------------|---------------------------------------|-----------------------|--------------------------|-------------------------|---------------------------------------|
| TIME (hour, date) | LAPSED TIME SINCE ** | PRES | SURE | - PROD. ZONE | REMARKS |
| | | Upper Completion | Lower Completion | TEMP. | |
| | | | | | |
| | | | | 1 | |
| | | | 1 | | |
| <u> </u> | | | | | |
| | | | • | i | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| · · · · · · · · · · · · · · · · · · · | | | | | · · · · · · · · · · · · · · · · · · · |
| | | <u> </u> | | | |
| Production rate d | uring test | | | | |
| | | | | | |
| Oil: | BOPI | D based on | Bbls. in | Hours | Grav GOR |
| | | | | | |
| Gas: | | MCFI | PD: Tested thru | (Orifice or Meter): | |
| | | | | · | |
| Remarks: | | | | | |
| | | | | | |
| | · · · · · · · · · · · · · · · · · · · | | | | |
| hereby certify th | at the informatio | on herein containe | d is true and con | aplete to the best of r | mu kaominina |
| | | | a so a de and con | apiete to the best of i | my knowledge. |
| Approved | | | _ 19 O ₁ | perator Amoco | Production Co. |
| New Mexico Oi | Conservation D | ivision | | | |
| 0 | المسادة المسالمة | HADIFE CHOLCON | Ву | Ralph Monto | ıya |
| | ginai Signed by C | HARLES GHOLSON | | | |
| By | M o CAC Menso | | Ti | de <u>Measuremen</u> | t Tech. |
| Title | OIL & GAS INSPEC | IOR, DIST. #3 | _ | 2.20.05 | |
| | | | Da | te <u>2-20-85</u> | |
| | | | | | |

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 exces

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questional le test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temp:ratures (gas zones only) and gravity and GOR (oil zones only).