COMP

Location of Well: J322605

Page 1

OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

#17

OIL COM. DIV.

Operator: AMOCO PRODUCTION COMPANY Lease/Well #: UTC CONTRACT 150 Meter #: 656 77 RTU: County:RIO ARRBIA NAME RESERVOIR OR POOL TYPE PROD METHOD PROD MEDIUM PROD UPR JIC CONTRACT 155 200 OCH 25677 GAS FLOW TBG COMP -1-161-1 / JIC CONTRACT 155 20E DK LWR 85360 GAS FLOW TBG COMP. 1-160-1 PRE-FLOW SHUT-IN PRESSURE DATA Length of Time Shut-In Hour/Date Shut-In SI Press. PSIG Stabilzed UPR 09/01/93 COMP LWR 09/01/93 COMP FLOW TEST DATE NO.1 Zone Producing (Upr/Lwr) Commenced at (hour, date) * PRESSURE TIME LAPSED TIME Prod SINCE* (hour, date) Upper Lower Temp. REMARKS 431 T. 429 C. 231 T. Both Zones SI 09/01/93 Day 1 429 C. 438 T. Both Zones SI 09/02/93 Day 300 T. 435 C 435 C. Both Zones SI 09/03/93 Day 442 T 350 T. 440 C. 440C 445 7 380 09/04/93 Day TURNED ON ZONE 450 C 450 C 09/05/93 Day 440 T. 335 T. 442 C. 329 T. 09/06/93 Day 441 T. 44/C. Production rate during test BBLs in ____ Hrs Oil: BOPD based on _ Grav___GOR ___ MFCPD: Tested theu (Orifice or Meter): METER Gas: MID-TEST SHUT-IN PRESSURE DATA Stabilized (yes/no) Length of Time SI | SI Press. PSIG Hour, Date SI UPR TOPE HA COMP LWR

(Continue on reverse side)

FLOW TEST NO. 2

Zone producing (Upper or Lower):

TIME (hour, dete)	LAPSED TIME	PRESONE		I PROD. ZONE I	
	\$INCE **	Upper Completion	Lower Completion	TEMP.	REMARKS
				 	
					
	<u></u>	<u> </u>		(
duction rate o	during test				
•				•	
l:	ВОР	D based on	Bbls. in	Hours.	Grav GOR
s:		MCFI	PD: Tested thru	(Orifice or Meter):	
				(
marks:					
arabu carrifu a	han sha !=6	1			
ereby certify t	hat the information	on herein containe		nplete to the best	
proved	OCT 2 1 19	993			
proved	on the information of the conservation of the	993			
proved New Mexico O	OCT 2 1 19 Dil Conservation D	993 Division	_ 19 O		of my knowledge. Moco broduction Con
proved New Mexico O	OCT 2 1 19 Dil Conservation D	993	19 O,	perator	moco broduction Con nan Woods
oproved New Mexico O	OCT 2 1 19 Dil Conservation D	993 Division	O	perator	moco broduction Con nan Woods I Technologist

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

commenced at (hour, date) **

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).