UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	Contract #108
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. S(()) /(d.)222
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
4 -:	Jicarilla C
well well other	9. WELL NO.
2. NAME OF OPERATOR	7E 10. FIELD OR WILDCAT NAME
Tenneco Oil Company	Basin Dakota
3. ADDRESS OF OPERATOR	11. SEC., T., R., M., OR BLK. AND SURVEY OR
P. O. Box 3249, Englewood, CO 80155 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.)	Sec. 13, T26N R5W
AT SURFACE: 1700' FSL 1670' FLE "J"	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	Rio Arriba New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	15 FLEWATIONS (SHOW DE KDR AND WD)
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	7270 YI.
	VED
FRACTURE TREAT RECEIVED	
SHOOT OR ACIDIZE	MOTE: Report results of multiple completion or zone change on Form 9–330.)
PULL OR ALTER CASING JUN 75	change on Form 9–330.)
MULTIPLE COMPLETE CHANGE ZONES U. S. GEOLOGI	change on Form 9-330.) JUL 2 - 1981
CHANGE ZONES ABANDON* U. S. GEOLOGI FARMINGTO	OIL COM.
(other)	DIST. 3
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta	te all pertinent details, and give pertinent dates
including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine	directionally drilled, give substitute locations and
6/11/81 - Drilled to TD of 8328'. Short trip. Circ and cond. POOH for logs.	
6/12/81 - Log w/Dresser. TIH. TOOH. Laid do	own drill pipe and collars.
6/13/81 - RU and run 1816' of 4-1/2" 11.6# STG	C K-55 csg and 2361' of 4-1/2"
10.5# STC K-55 csg. Shoe @ 8328'. Top of liner hanger @ 4137' Cmt w/300 sx 65/35	
POZ W/6% gel, .6% D-60. Tail in w/150 sx Class B w/.6% D-60. Plug down. Float	
held ok. Cmt circ'd to top of liner @ 3962'. Reversed out trace cmt. Release	
rig 6/12/81.	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct SIGNED WORLD ASST. DIV. Ad	m.Mgr.date6/18/81
(This space for Federal or State of	office use)

Acter ten für hebund

DATE _

*See Instructions on Reverse Side

JUL 01 198

BY ESPHINGED HOLS HELLE