

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
Box 3249, Englewood, CO 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 790' FNL & 1850' FEL "B"
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐
☐

(other) Commence Drilling Operations

RECEIVED

JUN 5

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5/19/81. MIRURT. Spud well 5/19/81 w/Four Corners rig #8.
5/20/81. Drill 12¼" hole to 355'. Short trip. Circ and cond hole. Run 8 jts (346') 9-5/8" 36# K-55 STC csg w/ shoe @ 347'. Cmt w/300sx Class B w/2% CACL₂ and 1/4#/sk Flocele. Plug down. Circ 23 bbls cmt to surface. WOC. Reduce hole to 8-3/4". Drill ahead.
5/24/81. Drill to 4360'. Short trip. TOOH. Laid down drill pipe and collars. Cross over from 4½" to 7" rams.
5/25/81. RU and run 99 jts (4354') 7" 23# K-55 STC csg w/shoe @ 4359', float collar @ 4322'. Circ and wash to bottom. Cmt w/550sx 65/35 POZ mix w/6% gel. Tail in w/150sx Class B. Plug down. Lost returns w/40 bbls. Est TOC @ 927'. Pumped maximum cmt pressure. WOC. NUWH. Pressure test to 1000 PSI. Blow down and dry hole. Resume drilling.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Carley J. Hatten TITLE Asst. Div. Adm. Mgr. DATE 6-1-81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

JUN 03 1981

RV Dean Elliott