

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY


**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)


1. oil ☐ gas ☒ other ☐  
well well well  
2. NAME OF OPERATOR  
Tenneco Oil Company  
3. ADDRESS OF OPERATOR  
P. O. Box 3249, Englewood, CO 80155  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
1670' FNL 1780' FWL  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:  
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:  
TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:



5. LEASE  
Contract 110  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Jicarilla  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Jicarilla A  
9. WELL NO.  
1M  
10. FIELD OR WILDCAT NAME  
Dakota/Mesa Verde  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 18, T26N R5W  
12. COUNTY OR PARISH  
Rio Arriba  
13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6614' gr.



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10/4/81 - RIH w/tbg, pmp out plug and SN. Tagged SD fill @ 7480'. CO to PBTD w/foam. Landed tbg in BOPS. Btm tbg @ 7350'. Kicked well around w/N2.  
10/7/81 - Kill well w/2% KCL. POOH w/tbg. Set 7" Model D w/expendable plug @ 4160'. Perf'd Chacra 4024-29', 4101-09'. RIH w/pkr, set @ 4000'. Acidize Chacra w/500 gals 15% wieghted HCL & 39 1.1 ball slrs. Released pkr & knocked balls off. POOH. Fracd Chacra dn csg w/70% foamed 2% KCL, 75,000 gals, 80,000# 20/40 SD.  
10/8/81 - Killed well w/2% KCL water, RIH w/tbg, cleaned SD off model D. Knocked out expendable plug. RIH w/2-3/8" tbg. F nipple seal assy, muleshoe & blast jts. Landed 2-3/8" tbg @ 7338'.  
10/9/81 - RIH w/tbg, F nipple, seal assy, muleshoe & blast jts. Cleaned SD off model D, knocked out expendable plug. Landed long string @ 4024'. Ran 1-1/4" tbg & SN for Chacra. NDBOP, NUWH, blew Chacra around w/N2. SWBD in Dakota. Left both sides flowing to CU. RDMOSU.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Andrew A. Patten TITLE Production Analyst DATE 10/19/81

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

NMOCC

ACCEPTED FOR RECORD  
OCT 26 1981  
FARMINGTON DISTRICT  
BY GAM