Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED	
Budget Bureau	No. 1004-0135
Expires: M	larch 31, 1993

5. Lease Designation and Serial No.

Contract No. 154

SUNDRY NOTICES AND REPORTS ON WELLS

6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservation Jicarilla Apache Use "APPLICATION FOR PERMIT—" for such pubposals 7. If Unit or CA, Agreement Designation MAR 3 1 1394 SUBMIT IN TRIPLICATE 1. Type of Well OIL CON DIV 8. Well Name and No. Oil Gas Well Jicarilla Apache No. 9E 2. Name of Operator 9. API Well No. 30-039-22589 Marathon Oil Company 3. Address and Telephone No. 10. Field and Pool, or Exploratory Area PO Box 2409, Hobbs, NM 88240 (505) 393-7106 Basin DK/Blanco MV 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State Unit Letter D Section 28, T-26-N, R-5-W Rio Arriba, CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Notice of Intent Change of Plans Abandonment **New Construction** Recompletion X Subsequent Report Plugging Back Non-Routine Fracturing Water Shut-Off Casing Repair Final Abandonment Notice Altering Casing Conversion to Injection Other Coiled tubing Dispose Water installation (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* On January 12, 1994, Marathon Oil Company initiated operations to install coiled tubing as a velocity string to produce the Basin Dakota and Blanco Mesa Verde pools. 1. Tag PBTD at 7496' with wireline. Open sliding sleeve at 5207'. 2. RIH w/2165' - 1.5" OD coiled tbg, 1.65" OD invertible packer, 5241' - 1.5" OD coiled tbg. 3. Set packer w/3000 1b compression at 5250' (top of pkr.) 4. Pump 37 BW. Install pack-off in coiled tubing wellhead/hanger. 5. Cut coiled tubing and install new tree assembly. 6. Pump 20,000 scf N2 to pump out coiled tubing plug. (1000 scf/min, max psi = 1400.) 7. Release N2 and turn on to pipeline. 8. Dakota producing up 1.5" coiled tubing. Mesa Verde producing up 1.5" x 2.375" annulus. 14. I hereby certify that the foregoing is true and correct R.J. Prosceno Title Petroleum Engineer (This space for Federal or State office use) MAR 3 0 1994 Chaif Lands sas Albert 18 activ SHIRLEY MONDY Approved by SHIKI Conditions of approval, if any:

or representations as to any matter within its jurisdiction.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements