

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 13807

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

BENSON-MONTIN-GREER DRILLING CORP.

3. ADDRESS OF OPERATOR

221 Petroleum Center Building, Farmington NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1685' FNL, 1860' FWL, Sec. 20, T-26N, R-1W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7724' GR

7. UNIT AGREEMENT NAME

CANADA OJITOS UNIT

8. FARM OR LEASE NAME

9. WELL NO.

22 (F-20)

10. FIELD AND POOL, OR WILDCAT

Puerto Chiquito Mancos

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

West

Sec. 20, T-26N, R-1W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-26-81 TD 8400' in 6-3/4" gas-drilled hole. Ran 29 joints (1321.21' TO, 1327.1' overall) 5 1/2" OD 17# K-55 ST&C Range 3 casing. Overall length of liner 1335' including cementing equipment and liner hanger. Ran on 3 1/2" OD IF drill pipe. Top of liner 7061' RKB.

Pumped 10 barrels gel water, then 20 barrels chemical wash. Cemented with 140 sacks Class H with 1.3% D-13 retarder and 0.2% D-60 fluid loss additive. Set liner hanger pack-off. Loaded annulus and reverse circulated above liner. Recovered water cut cement.



18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Vice-President

DATE 12-2-81

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NMOCC

K