917-251

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

be used for reporting packer leakage tests in Southeest New Mexico

555								
erator A	moco Produ	uction Co.	Lease	Rome	-0 G	m	Well No.	001
ation Well: Unit <u>L</u>	2 Sec. 25	Г w p. <u>26</u>	Rge	06		Cour	nty <u> </u>	Arriba
	NAME OF RESERVO	TYPE OF PROD. (Oil or Goe)		METHOD OF PROD. (Flow or Art. LHT)		•	PROD, MEDIUM (Tbg. or Cog.)	
pper plotion	Chacca				4.			
plotten /	Mysa Ve	erde			·		=	
		PRE-FL	OW SHUT-IN P	RESSURE	DATA		*	
pper pletten	' ·		Length of time shut-in		81 proce. polg 392 Stabilized? (You or Ho)			
	Hour, date shut-in		Length of time shut-in				Stabilized? (Yes or No) UES	
			FLOW TEST	NO. 1	4.		7	
monood at thour, d	nto)#			Zono producing (Upper or Lower):				
TIME LAPSED TIME		PREI Upper Completion	PRESSURE Ipper Completion Lower Completion		PROD. ZONE		REMARKS	
1/20/92		391	682			SZ	Bo	the Jone
1/21/92	·	391	682				•	
1/22/92		392	683			,		
1/23/92	-	389	684			Flo	n &	over 30 an stolen
124/92		391	486	_		Purchas	rer Po	
1/25/92	<u> </u>	390	674	<u> </u>				
duction rate	during test		. •				•	•
:	BOP.	D based on	Bbls. i	Δ	_ Hours.		Grav	GOR
s:		мс	FPD; Tested thn	ı (Orifice	or Meter)	:	•	· · · · · · · · · · · · · · · · · · ·
•		MID-T	EST SHUT-IN P	RESSURE	DATA			
Hour, date	* }		Longth of time shut-in		SI press, pelg		Stabilized? (Yee or No)	
	Hour, date shut-in		Longth of time shut-in		SI press. polg		Stabilized? (Yes or No)	
				3	Same of the same o	D E		

FEB2 0 1002

(Continue on reverse side)

OIL CON. DIV. DIST. 3,

FLOW TEST NO. 2

Zone producing (Upper or Lewer):

TIME (hour, date)	LAPSED TIME	PRESSURE		PROD. ZONE	_	
	SINCE **	Upper Completion	Lower Completion	TEMP.	REMARKS	
				1		
	·					
, — , .	 					
		1	<u> </u>	<u> </u>	<u>.</u>	
		мс		(Orifice or Meter	r):	
ereby certify (that the informat	ion herein contain	ned is true and o	omplete to the be	est of my knowledge.	
pproved New Mexico C	Oil Conservation	Division	17	Operator	1 1	
				By	san Woods	
, <u>Odana</u>	of Signed by CHA!	RLES GHOLSON		Title	son Woods wield Dech	
Title DEPUTY OIL & GAS INSPECTOR, DIST. #3				_		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever temedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Commenced at flour, date) **

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than area days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shart-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shot-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no lenk was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).