

NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

AZTEC DISTRICT OFFICE
1000 RIO BRAZOS ROAD
AZTEC NM 87410
(506) 334-6178 FAX: (505) 334-6170
http://www.rd.state.nm.us/ocd/District III/3distric.htm

OIL CONSERVATION DIVISION

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Page 1 Revised 11/16/98

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator $_{oldsymbol{_I}}$	ouis Dreyf	us'Nat. Ga	s_Lease Nai	me <u>Mile</u>	es Federal	Well No1-A			
_ocation of	Well:Unit Lette	r_F_Sec_	<u>5 Twp 2</u>	<u>6N</u> Rge_7 <u>W</u>	7_API#30-0_39-	-22916			
	NAME OF RESERVOIR OR POOL		1	F PROD. or Gas)	METHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)			
Upper Completion	Otero Chacra		g	as	flow	tbg.			
Lower Completion	Blanco Mesa Verde		g	as	flow	tbg.			
		PRE-	FLOW SHUT4	N PRESSUF	RE DATA				
Upper Completion	Hour, date shut-in 9/5/99		Length of time 3 day		SI press. Psig 210	Stabilized? (Yes or No) Yes			
Lower Completion	Hour, date shut-in 9/5/99		Length of time 3 day		SI press. Psig 200	Stabilized? (Yes or No) Yes			
			FLOW TE	ST NO. 1					
Commenced at (I	hour, date)*			Zone producing (Upper or Lower): 1 OWET					
TIME (hour,date)	LAPSED TIME SINCE*	PRESS	SURE	PROD. ZON TEMP.	REMARKS				
	311402	Upper Completion	Lower Completion	TEMP.					
9/8/99	1 day	215	108			26118133			
9/9/99	2 days	215	110			JAN 2000			
					60 -	JAN 2000			
					(0)	O'L CON DIV			
					\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\				
oduction rat	te during test	•				81588 B. C. S.			
il:		BOPD based	on	Bbls. in	HoursG	ravGOR			
as:2	226	MCFP	D; Tested thru		meter				
		MID-1	TEST SHUT-IN	PRESSURI	E DATA				
Upper Completion	Hour, date shut-in		Length of time s		SI press psig	Stabilized? (Yes or No)			
Lower Completion	Hour, date shut-in		Length of time s	shut-in	St press, psig	Stabilized? (Yes or No)			

FLOW TEST NO. 2

Commence	d at (hour, date)*	······		Zone producing (Upper or Lowr):				
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion	URE Lower Completion	PROD. ZONE	REMARKS			
Production ra	te during test							
				inHour rfice or Meter):	sGravGOR	 -		
hereby certif	y that the inform	nation herein cor	tained is true and	d complete to the	bes of my knowledge.	-		
Approved JAN 12 20009			_ Operator_ By_\\	Operator 6410 DRAYEUS NATIDAL GAS				
DEPUTY	. SIGNED BY CHAI	rlie T. Perimin Ctor, dist. #3	Title	Title				

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial
- packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at lifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at teast one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result's of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage. Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).