

NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION
AZTEC DISTRICT OFFICE
1000 RIO BRAZOS ROAD
AZTEC NM 87410
(506) 334-8178 FAX: (506) 334-8170
http://www.nrd.state.nm.us/ocd/District Ill/3distric.htm

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Page 1 Revised 11/16/98

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator <u>I</u>	ouis Dreyfu	s Matural	GasLease Na	meMKL	·		Well No 16-R
Location o	of Well:Unit Letter	rJSec_	_5_Twp_2	<u>6N_</u> Rge	7W_A	API # 30-0 <u>39</u> -	-22917
	NAME OF RESI		TYPE OF PROD. (Oil or Gas)		METHOD OF PROD. (Flow or Art, Lift)	PROD.MEDIUM (Tbg. or Csg.)	
Upper Completion	South Bla	anco P.C.	gas	gas		flow	tbg.
Lower Completion	Otero Cha	acra	gas	gas		flow	tbg.
		PRE	FI OW SHIT	N DDESCIII	PE D	A.T.A	
Upper	Hour, date shut-in		Length of time	_OW SHUT-IN PRESSUF		ress. Psig	Stabilized? (Yes or No)
Completion	9/5/99	1	3 days		80	yes	
Lower	Hour, date shut-in			Length of time shut-in		ess. Psig	Stabilized? (Yes or No)
Completion	9/5/99	l	3/days		200	yes	
				ST NO. 1			100
Commenced at	l (hour, date)*				g (Uppe	rorLower): lower	
TIME (hour,date)	LAPSED TIME SINCE*	PRES	SSURE			10#61	REMARKS
		Upper Completion	Lower Completion	1 (2.0%)			of the later of th
9/8/99	1 day	80	104			15 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
9/9/99	2 days	80	109			A.	1/4/1
						4	JAN 2000 RECEIVED
						12	DIL CON. DIV
							DIST. 3
					- Constant		300
Production ra	ate during test						65.75.35.03 (C. S. C. S.
Dil:		BOPD based	l on	Bbls. in		_Hours Gr	
as:	102		PD; Tested thru				avGOR
			TEST SHUT-IN		,		
Upper Completion	Hour, date shut-in		Length of time shut-in		ss psig	Stabilized? (Yes or No)	
Lower Completion	Hour, date shut-in		Length of time sh	Length of time shut-in		ss. psig	Stabilized? (Yes or No)
	•		(Continue on r	everse side)		magn. Ct	9

FLOW TEST NO. 2

Commence	d at (hour, date)*	·•		Zone producing (Upper or Lowr):				
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion	URE Lower Completion	PROD. ZONE	REMARKS			
Oil: Gas:		based onMCFF			sGravGOR	-		
hereby certif	···		tained is true and	d complete to the	bes of my knowledge.			
Approved19 Mexico Oil Conservation Division			Operator_	Operator DeEVEUS NATURAL COAS By Mi. Ve Zammen				
Ву			Title					
Title			_ Date	Date of 15/00				

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shuf-in for pressure stabilization. Both zones shall remain shuf-in until the well-head pressure in each has stabilized, provided however, that they need not remain shuf-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial

packer leakage test, a gas welf is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at lifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests; all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result's of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).