

## NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION
AZTEC DISTRICT OFFICE
1000 RIO BRAZOS ROAD
AZTEC NM 87410
(506) 334-6178 FAX: (505) 334-6170
http://www.nd.state.nm.us/ocd/District III/3distric.htm

it as form is not to be used for reporting packer leakage tests in Southeast New Mexico

Page 1 Revised 11/16/98

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator	ouis Dreyfi	is Natural G	<u>a s</u> ease Na	meFea	erel	Well No8-22
_ocation of	Well:Unit Lette	r <u>F</u> Sec <u>8</u>	Twp26	5 <u>N_Rge_7</u>	W_API#30-0 <u>39</u>	9-22933
	NAME OF RES	ERVOIR OR POOL	TYPE OF PROD. (Oil or Gas) gas		METHOD OF PROI (Flow or Art, Lift)	D. PROD.MEDIUM (Tbg. or Csg.)
Upper Completion	Mesa Vei	rde			flow	tbg.
Lower Completion	Dakota		gas		flow	tbg.
		PRE-F	LOW SHUT-	N PRESSUR	RE DATA	
Upper	Hour, date shut-in		Length of time	shut-in	SI press. Psig	Stabilized? (Yes or No)
Completion	11/26/200	11/26/2000		ys	390	yes
Lower	Hour, date shut-in		Length of time	shut-in	SI press. Psig	Stabilized? (Yes or No)
Completion	11/26/200	00	3 day			yes
			FLOW T	EST NO. 1	· <del></del>	
commenced at i	(hour, date)*			Zone producing	g (Upper or Lower):	lower
TIME (hour,date)	LAPSED TIME SINCE	PRESSURE		PROD. ZONE		REMARKS
		Upper Completion L	Upper Completion Lower Completion			
11/29	1 day	390	420			at a
11/30	2 days	390	161		63	450/80
12/01	3 days	390	156			* 0)
				<del></del>		DEC 2000
	<del> </del>					
<del></del>			<del></del>			LOON DIV
			·		The state of the s	001.3 S
oduction ra	te during test					22 2 0 0 0 J
l: BOPD based on			n	Bbls. in		GravGOR
as:	106		; Tested thru		-	
		MID-TE	EST SHUT-IN	I PRESSURI	E DATA	
Upper Completion	Hour, date shut-in		Length of time shut-in		SI press psig	Stabilized? (Yes or No)
Lower Completion	Hour, date shut-in Length of t		Length of time s	shut-in	SI press. psig	Stabilized? (Yes or No.)
			<del></del>		L	1

FL	.OW	TEST	NO.	2

Commenced at (hour, date) <sup>™</sup>				Zone producing (Upper or Lowr):		
TIME (hour,date)	LAPSED TIME Since**	PRESSI Upper Completion		PROD. ZONE	REMARKS	
					·	
Oil: Gas:		based onMCFP		. inHour Orfice or Meter):	sGravGOR	
Approved_ Mexico Oil Con ORici By	UEC	19_	Operator_ By	I Rain	bes of my knowledge.	New 

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Civision.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion
  are shut-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain
  shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note; if, on an initial
- packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a proeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests; immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests; all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result's of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).