Form 3160-5 (August 1999)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

DORLING OF EA	2011232	5. Lease Serial No.
Do not use this form for proposals to drill or to re-priter		Jicarilla Contract 117
		6. If Indian, Allottee or Tribe Name
abandoned well. Use For	m 3160-3 (APD) for such Proposals (	
CUDAIT IN TOID LOATE	Other instructions on reverse side	
SUBMIT IN TRIPLICATE -	Other instructions on reverse side	7. If Ollit of CA/Agreement, Name and/or
1. Type of Well	100 000	7
Oil Well X Gas Well Other		8. Well Name and No.
2. Name of Operator		Jicarilla 117E 5A
ENERGEN RESOURCES CORPORATION		9. API Well No.
3a. Address 3b. Phone No. (include area code)		30-039-22979
2198 Bloomfield Highway: Farmington 4. Location of Well (Footage, Sec., T., R., M., or Survey)		10. Field and Pool, or Exploratory Area
1090' FSL, 1650' FWL, Sec. 34, T26N	- '	Blanco Mesaverde
		11. County or Parish, State
F - 28		Rio Arriba NM
12. CHECK APPROPRIATE	BOX(ES) TO INDICATE NATURE OF NOTICE, F	
TYPE OF SUBMISSION	TYPE OF ACT	ION
Notice of Intent	Acidize Deepen Produ	uction (Start/Resume) X Water Shut-Off
<u> </u>	Alter Casing Fracture Treat Recla	umation Well Integrity
X Subsequent Report		
Final Abandonment Notice		porarily Abandon
	Convert to Injection Plug Back Wate	r Disposal
Attach the Bond under which the work will be per following completion of the involved operations. I testing has been completed. Final Abandonment I determined that the final site is ready for final inspect 5/8/01 MIRU. ND wellhead, NU BOP. 5/9/01 Finish TIH w/scraper to 59 Reset packer @ 5412'. 5/10/01 Squeeze Cliff House perf 5/11/01 TOH w/packer. TIH w/bit, 5/14/01 Drill cement to 5788'. TO 5/15/01 TIH w/mill, drill out CI	Nete horizontally, give subsurface locations and measured and truformed or provide the Bond No. on file with BLM/BIA. Requif the operation results in a multiple completion or recompletion Notices shall be filed only after all requirements, including reclaration.)  Release packer & TOH w/207 jts. 2-3/8" tu 00'. TOH. TIH w/CIBP, set @ 5819'. TIH w/p s 5647'-5766' w/100 sks "B" w/2% cac12 & tag cement @ 5584'. Drill cement to 5708'. H. TIH w/packer & test squeeze to 1000 ps BP @ 5819' & clean out to PBTD @ 6522'. To ubing, land @ 6240', SN @ 6209'. RDMO.	red subsequent reports shall be filed within 30 day in a new interval, a Form 3160-4 shall be filed one mation, have been completed, and the operator ha ubing. TIH w/bit & scraper. backer, test CIBP to 2000 psi.  3% Halad-9(119 cu ft).
14. I hereby certify that the foregoing is true and correct	Title	
14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)  Don Graham	Drilling/Compl	etion Foreman
Now Fraham	Date 5/18/01	
THIS	SPACE FOR FEDERAL OR STATE OFFICE USE	
Approved by /s/ Patricia M. Hes	ster Laffids and Mineral Fleak	HITAY 2 2 2001
Conditions of approval, if any, are attached. Approval of certify that the applicant holds legal or equitable title to which would entitle the applicant to conduct operations of	those rights in the subject lease	7.77. 2.2. 2001