## UNITED STATES

OHITED STATES	5. Lt () :		
DEPARTMENT OF THE INTERIOR	Contract #104		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
dedecate content	Jicarilla Apache		
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME		
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME		
1 011 035	Jicarilla $\mathcal{E}$		
1. oil gas well other	9. WELL NO.		
2. NAME OF OPERATOR	Æ-10-E		
Southern Union Exploration	10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR	Wildhorse Gallup/Basin Dakota		
314 N. Auburn Drawer "F" Farming on, NM	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA		
helaw.)	Sec. 22, T26N-R4W		
AT SURFACE: 1000' FNL & 1850' FEL	12. COUNTY OR PARISH 13. STATE		
AT TOP PROD. INTERVAL: Same	Rio Arriba New Mexico		
AT TOTAL DEPTH: Same	14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,			
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6805' GL:		
	COLINA		
TEST WATER SHUT-OFF U U STRACTURE TREAT STRACTURE TREAT			
SHOOT OR ACIDIZE			
REPAIR WELL 日 日 日 日 日 日 日 日 日 日 日 日 日 日 日 日 日 日	(NOTE: Report results of multiple completion or zone		
PULL OR ALTER CASING [] [] [] [] [] [] [] [] [] [] [] [] []	1002 change on Form 9-340.) 101 8 1382		
MULTIPLE COMPLETE JUN 291	OIL CON. COM.		
CHANGE ZONES	1		
ABANDON* U CLUMAN (other)			
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stational including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertined tower Dakota was perforated from 7794-7800 and	directionally drilled, give subsurface locations and ent to this work.)*		
holes-IJSPF. Lower Dakota was treated with 2	5 bbl's 15% HCL Acid. 150,000#		
20/40 sand and 73,500 gal mini max 3-40 w/2%			
20, 10 00110 1114 10,000 822 11212 11111 0 12 11 11			
Upper Dakota was perforated from 7675 to 7695 treated $w/25$ bbls 15% HCL Acid. 41,650 gal m 20/40 sand.	, 1 JSPF, 21 holes .36" inimax 3-40, w/2% HC and 85,000 $\%$		

Work was compleated 6-18-82.

			<b>C</b> + O	r.
Subsurface Safety Valve: Manu. and T	ype		Set @	rt.
18. I hereby certify that the foregoing	is true and correct			
SIGNED LES ASUS	TITLE	DATE		
	(This space for Federal or St	tate office use)		
	TITI C	DATE	· · · · · · · · · · · · · · · · · · ·	
APPROVED BY	11112			T. 1 44 24 4 1 1 1 1 24

\*See Instructions on Reverse Side

JUL 7 1982

NMOCC