STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

o (14	nion Texas	- Petroley	m lesse)ica	ille	∪1F"	Well 7				
Operator <u>\(\alpha\)</u> Location	11 20	21 A/	Rge	4101		C	Rio arriba				
of Well: Unit _	K Sec. 28 T	wp	TYPE OF PRO			THOD OF PROD.	PROD. MEDIUM				
	NAME OF RESERVO	R OR POOL	(Oil or Gae			Now or Art. Lift)	(Tbg. or Ceg.)				
Upper Completion	Has	Has Flo		wing.	Tubing						
Lower Completion	- 1 61 . D			- Flouring		urng.	Tubing				
			W SHUT-IN PR	ESSURE	DATA						
Hour, dat	te shul-in 9:00 A.Y.	7) . Length of time shut		Si press. psi	649		bilized? (Yes or No)				
Completion: ///	/9/88 le shut-in	Length of time, shuj	do .	SI press. paig			ibilized? (Yes or No)				
Lower Completion	knew	unkn	our !	-	-0-		Yes				
L			FLOW TEST N	NO. 1							
Consmenced at (hour.	date)* ///22/	88 9:00	A.M.		ducing (Upp	er or Lowertz	pper				
TIME	LAPSED TIME	PRESS		PROD.		,	REMARKS				
9:00 A.M	SINGE*	Upper Completion	Lower Completion	TEI							
11/20/88	/day	585									
9:00 A.M.	2 days	638	-0			<u> </u>					
9:00 A.M.	3 days	649	-0								
9:00 A.M.		280	-0	50) "						
9:00 A.m	\$ 4 days	350_	-A	50	 						
1//017/106	s any				 •						
Production rate	e during test	<u></u>		<u> </u>		. 					
FIUGULUUM 120	-		m: .	_	Hours	Gra	av GOR				
Oil:	BOP	D based on	Bbls. in								
Gas:		MCF	PD; Tested thru	(Orifice	or Meter): me	ter				
MID-TEST SHUT-IN PRESSURE DATA											
Hour, d	ate shul-in	Length of time sh	ut-in	SI press. p:	Prg Pr	S	tabilized? (Yes or No)				
Completion Hour, d	late shut-in	Length of time sh	ul-in	Si press. pr	nig	, , s	tabilized? (Yes of No.				
Completion							\$ 40 E 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				

The second of the

FLOW TEST NO. 2

ommenced at (hour, d	ate) **		¿ Zone producing (Upper or Lower):					
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE				
		Upper Completion	Lower Completion	TEMP.	REMARKS -			
				<u> </u>	Supplied to the supplied to th			
			<u> </u>	•				
	·							
					<u>:</u>			
oduction rate o	during test	<u> </u>						
11:	ВОР	D based on	Bbls. in	Hours.	Grav GOR			
ıs:		МСР	PD: Tested thru	(Orifice or Meter):			
•				· 				
hereby certify t	hat the informati	on herein contain	ed is true and co	mplete to the bes	t of my knowledge.			
pproved	•	1989	19	Operator Ung	ion Texas Petroleun La Morman Luction Technici			
Origin	al Signed by CHAF	RLES UNULUUN	B	y Baila	ia Morman			
DEL		ISPECTOR, DIST. #3	Т	1/2/22				
tie				Date	8 9			

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever temedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previous ly shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweigh pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-petiod, at fufteen-minute intervals during the first hour thereof, and a hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midwapoint) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tens: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Aziec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revisec 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).