STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

| | | - 26N | | , | illa | E No | | |
|--|--------------------------------|------------------------|------------------------|----------|--|-------------|---|--|
| went onto | Well: Unit K Sec. 28 Twp. 26 N | | | ROB. | METHOD OF PROD. (Flow or Art. Lift) | | PROD. MEDIUM (Tbg. er Ceg.) | |
| Upper Completion M. D. M. M. A. D. A. | | | Aus | | flowing | | Tubing | |
| Lower Completion Dakota | | | Yas | | Flowing Flowing | | Tubing | |
| | | PRE-FLO | W SHUT-IN PF | RESSURE | DATA | 0 | 0 | |
| Upper completion: ///2 4/89 5 de Length of time et Lower | | : 5 da | 5 days | | 700 | | Stabilized? (Yes or No) Stabilized? (Yes or No) | |
| | | 1 unkno | | | | | | |
| | | | FLOW TEST I | NO. 1 | | | , | |
| onsmenced at (hour, da | 101 + 11/28/89 | | 8:00 A.M. | | ducing (Upper or | LOWER UPPLU | | |
| TIME (hour, date) | LAPSED TIME SINGE* | PRESS Upper Completion | Lower Completion | PROD. | 4 | RI | MARKS | |
| 8:00 A.M. | 1day | 683 | 12 | | | | | |
| 8:00 A-m | 2 days | 698 | /2 | | | | | |
| 8:00 A.M. 11/28/89 | 3 days | 700 | 12 | | | | | |
| 8:00 AM 11/29/89 | 4 days | 266 | 12 | 58 | | | | |
| 8:00 A.m. 11/30/89 | 5 days | 29.3 | <u>/2</u> | 58 | 3 | | | |
| Production rate of | luring test | | | | | | | |
| Oil: | BOPI | D based on | Bbls. in | l | _ Hours | G12V | GOR | |
| Gas: | | мсғ | D; Tested thru | (Orifice | or Meter): _ | meter | <u></u> | |
| | | MID-TE | ST SHUT-IN PI | RESSURE | DATA | | | |
| Upper Completion Length of t | | | ne shut-in SI p | | l press. psig | | 17 (Yes or No) | |
| Lower Completion | | Length of time shu | Length of time shul-in | | Si press. palg | | OF BUT E | |
| | | | | | | K | | |
| | , | | | | | IJı | C1 5 1989 🔭 | |

FLOW TEST NO. 2

| | | | | Zone producing (Upper or Lowerk | | | | | | |
|---|-------------------------|-------------------------|------------------|---------------------------------|---------------------------------------|--|--|--|--|--|
| TIME | LAPSED TIME SINCE ** | PRESSU Upper Completion | RE | PROD. ZONE | REMARKS | | | | | |
| | | Spen Completion | Completion . | itmr. | | | | | | |
| | | | • | | For the second of the second of | | | | | |
| | | 1 | : | : | | | | | | |
| | - | | · | | | | | | | |
| | | | ! ! | | • | | | | | |
| | | | | · | | | | | | |
| | | | i ! | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | - | | | | | | | |
| | .1 | | 1 | l | | | | | | |
| roduction rate o | during test | | | | | | | | | |
| \'1 | | | | | | | | | | |
| ·u: | ВОР | D based on | Bbls. in | Hours. | Grav GOR | | | | | |
| ias: | | MCFPI | D: Tested that (| (Orifice or Meter): | | | | | | |
| | _ | | | Condition of Metery. | | | | | | |
| cmarks: | | | | | · · · · · · · · · · · · · · · · · · · | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| hereby certify t | hat the informati | on herein contained | is true and con | unlese to the best | of my knowledge | | | | | |
| • | DEC 1 E 1 | 1000 | | | | | | | | |
| bbtoseq — | DEC 19 | 989 | 19 O | perator <u>Uni</u> | on Texas letioleun | | | | | |
| New Mexico C | Oil Conservation I | Division | | 11. | $\mathcal{M}_{\mathbf{a}}$ | | | | | |
| 0-:-! | I Signed by CHARI | ES GAOLSON | Ву | 1 Bowa | in Mouran | | | | | |
| Origina | ii Signed by Chara | LES Officesor. | τ; | ic Read | in Norman uction Technicia | | | | | |
| , | | aren DICT #2 | | | , | | | | | |
| itie DEPUTY OIL & GAS INSPECTOR, DIST. #3 | | | | Date 12/12/89 | | | | | | |
| | | | | • | • | | | | | |

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture unatment, and whenever temedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Text No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such text shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage text, a gas well is being flowed to the aumosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 5 above.
- Flow Ten'No. 2 shall be conducted even though no leak was indicated during Flow Ten Fig. 1. Erroredure for Flow Ten No. 2 is to be the same as for Flow Tent No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fureen-minute intervals during the first hour thereof, and at houtly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tents: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).