5. LEASÉ

## **UNITED STATES** DEPARTMENT OF THE INTERIOR

DEPARTMENT OF THE INTERIOR	Jicarilla Contract 155
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
GEOLOGICAL SORVET	Jicarilla Apache
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas X other	Jicarilla Gas '.om 155A
Well C Well Other	9. WELL NO.
2. NAME OF OPERATOR Amoco Production Company	10. FIELD OR WILDCAT NAME Otero Chacra/Gonzales Mesaverde
3. ADDRESS OF OPERATOR 501 Airport Dr., Farmington, NM 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	T26N, R5W
AT SURFACE: 1800' FNL x 850' FEL	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	Rio Arriba NM
AT TOTAL DEPTH: Same	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	30-039-22553 15. LEVATIONS (SHOW DF, KDB, AND WD)
REPORT, OR OTHER DATA	15. TLEVATIONS (SHOW DF, KDB, AND WD) 6664' GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	\$D 0004 GE
TEST WATER SHUT-OFF	
FRACTURE TREAT	5
SHOOT OR ACIDIZE	(NO) E: Report results of multiple completion or zone
PULL OR ALTER CASING	SUM. enange on Form 9–330.)
MULTIPLE COMPLETE	W. W.
CHANGE ZONES	
ABANDON* LI Corrected Completion Report	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertined.)	directionally diffied, give substitutes required
Completion operations commenced 12-4-82. Tot plugback depth is 5409'. Perforated interval 5286', 5280-5268', 5264-5260' w/2jspf, a tota 5345-5260' with 54000 gallons of 20# gelled w factant per 1000 gallons frac fluid and 70000 5180-5218' w/2 jspf, a total of 76 .40" hole 49000 gallons of 20# gelled water containing 1000 gallons and 76000# 10-20 mesh sand. Set tubing at 5308'. Land 1-1/4" tubing at 3965'	s 5345-5341', 5306-5300, 5290- l of 60 .4" holes. Fraced interval ater containing 2% KCL, 1 gal. sur- # 10-20 mesh sand. Perforated interval s. Fraced interval 5180-5218' with 2% KCL, one gallon surfactant per packer at 4030'. Land 2-1/16"
Subsurface Safety Valve: Manu, and Type	Set @
18. Thereby cortify that the foregoing is true and correct Ulginal Signal Ba	
SIGNED B.T. Roberson TITLE Admin. Sup	office use)
	DATE
APPROVED BY	DATE
CONDITIONS OF THE PROPERTY OF	

\*See Instructions on Reverse Side

