

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
Ladd Petroleum Corporation

3. ADDRESS OF OPERATOR
830 Denver Club Bldg. Denver, Colo. 80202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1700' FSL, 1580' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
USA SF 079161

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Lindrith

9. WELL NO.
24M

10. FIELD OR WILDCAT NAME
Basin Dakota - *Large Saline*

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 4-T-26N-R7W

12. COUNTY OR PARISH
Rio Arriba

13. STATE
N. Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6574' GR

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

RECEIVED
FEB 28 1983
U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.
XXX 5 1/2" casing and cement.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 183 jts 5 1/2" J-55 casing and set at 7348'. Bottom 496' was 17# and remainder was 15.5#. Cemented 1st stage w/225 sxs (260 Ft³), 50/50 Poz, 2% gel, and 100 sxs (115 Ft³) Class "B". Second stage: (Dv @ 5462') w/200 sxs (230 Ft³) 65/35 Poz, 12% gel, and 50 sxs (58 Ft³) Class "B", third stage: (DV @ 3281') w/225 sxs (260 Ft³) 65/35 Poz, 12% gel, + 50 sxs (58 Ft³) Class "B". Good returns throughout, Circ. 2 bbls to surface. Plug down @ 3:00 P.M. 2/24/83. Bump with 1000 psi, held o.k. Rig released @ 4:00 P.M. 2/24/83.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Drilling Engineer DATE 2-25-83

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE ACCEPTED FOR RECORD
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NMOCC