## STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

## OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests

	leskage tests east New Mexico	NORTHWEST N	ew mexico p	ACKER-LEAKA	JE 1ESI		
•	JESTAR		Lease _	Lindrith		Well 24M	
erator					Count	RA RA	
ation Well: Unit K Sec. 4 Twp. 26N			TYPE OF P	ROO.		PROD, MEDIUM (Tbg. or Ceg.)	
NAME OF RESERVOIR OR POOL			(OII or G	es)	(Flow or Art LIN)	ł.	
Ipper Gallup			0il		Flow	Tbg	
parer Dakota			Gas	Flow		Tbg	
		PRE-FLO	W SHUT-IN F	RESSURE DATA			
oper Hour, date shut-in Length of time oper pletion 11:45 am 8-7-98 3 d		Length of time shut	-In	SI press. psig 4720 Si press. psig	1°	Stabilized? (Yes or No)  Stabilized? (Yes or No)	
Hour dat	Hour, date shut-in Length of time 11.45am 8-7-98 30		14n 4 <u>5 -                                    </u>	160		No	
bletion (C .42	am o i is		FLOW TEST	NO 1			
	date)* 1145am	8-10-98	FLOW 1EST	Zone producing (U	opper or Lower): (	DWE	
TIME	LAPSED TIME	PRESS	SURE Lower Completion	PROD. ZONE TEMP.		SEP 2 5 1998	
(hour, date)	2 days	Upper Completion  440	34				
					OUL	GON. DUV.	
					Sec. 17. 17. 18. 18. 18. 18. 18. 18. 18. 18. 18. 18		
duction rate	e during test						
l:	201	PD based on MCF	PD; Tested the	in Hou ru (Orifice or Me	rs G ter):G	Grav GOR	
us:	<u></u>			PRESSURE DAT			
Upper	ate shut-in	Length of time shi		Si press. psig		Stabilized? (Yes or No)	
Lower Hour, d	ate shut-in	Length of time sh	ut-in	SI press. paig		Stabilized? (Yes or No)	

FLOW TEST NO. 2

TIME	(e) * *	PRESSURE		Zone producing (Upper or Lower):		
flour, date)	LAPSED TIME SINCE **	Upper Completion	Lower Completion	PROD. ZONE TEMP.	REMARKS	
		··- ·				
				<u> </u>		
					······································	
narks:		MCFP	D: Tested thru (O	rifice or Meter):	Grav GOR	
	the information			ete to the best of m	y knowledge.	
proved lew Mexico Oil C	Conservation Div	ision	19 Oper	QUESTAR		
Droved New Mexico Oil C ORIGINAL SIGN	Conservation Div	ision	19 Oper By _	extor QUESTAR  Learns.	Hanhardt	
proved New Mexico Oil C ORIGINAL SIGN	Conservation Div. SEO BY CHARLIE	ision	19 Oper By _ Title	QUESTAR	Hanhardt	

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadwright pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the mic way point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).