Form	3160	)_5
(Nove	m Der	1983)
(Form	erly	9 - 331)

WELL

## UNITED STATES DEPARTMENT OF THE INTERIOR verse side

SUBMIT	IN	TRIPL	ICA:	E.
(Other 1	DStr	BEEQUITOR'S	<b>60</b>	74
Term mide	٠ ١			

r orn. approvec. Budget Bureau No. 1004-0135

Expires August 31, 1985

6. IF INDIAN, ALLOTTEE OR TRIPE NAME

5.	LEASE	DESIG	MOTTAK	AND	BERLAL	<b>F</b> (
Ji	cari	11a	Apac	he	102	/

SUNDRY	NOTICES	AND	REPORTS	ON WELLS

BUREAU OF LAND MANAGEMENT

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.)

Jicarilla Apagne	
 7. UNIT AGREEMENT NAME	_
 	_
8. FARM OR LEASE HAME	
 Jicarilla Apache 102	
9. WHAL NO.	
~ · ·	

3. ADDRESS OF OPERATOR 2325 East 30th Street, Farmington, NM 87401

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\* bee aiso space 17 below.)
At surface

Blanco Mesaverde 11. SEC., T., E., N., OR BLE. AND SURVEY OR AREA

10. FIELD AND POOL, OR WILDCAT

970' FNL x 1110' FWL

Amoco Production Company

NW/NW Sec 3, T26N, R4W

11. ELEVATIONS (Show whether DF, RT, GR. etc.) 14 PERMIT NO. 7158' GR

OTES

12. COUNTY OF PARISE 15. STATE Rio Arriba


1C.

Check Appropriate Box To Indicase Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:			EDBSEQUENT REPORT OF ;		
TEST WATER SHUT-OFF		PULL OR ALTER CASING MULTIPLE COMPLETE		WATER BHUT-OFF FRACTURE TREATMENT	ALTERING CABING
SHOOT OF ACIDIZE		ABANDON*	i—	SHOOTING OF ACIDIZING	ABANDONMENT*
nepain well (Otder)		CHANGE PLANS		(Other) (Norr: Report results of m Completion or Recompletion	ultiple completion on Well heport and Log form.

17. DESCRIBE PROPOSED OF COMPLETES OPERATION: (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Moved in and rigged up service unit on 3-21-88. Set a castiron bridgeplug at 5015' and spotted 10 gals sand on top. Isolated casing leaks from 3221' - 3435'. Set a cement retainer at 3323' and squeezed with 118 cf Class B cement. Milled out cement and retainer. Landed 2-3/8" tubing at 2491'. Released the rig on 4-4-88.



18. I hereby certify that the foregoing is true and correct SIGNED		DATE 4-11-88
(This space for Federal or State office use)		
APPROVED BY	TITLE	DACCEPTED FOR RECORD

\*See Instructions on Reverse Side

APR 20 1988 **FARMINGTON RESOURCE AREA**