

RECEIVED
JAN 10 1984
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
OIL & GAS DIV.

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR

El Paso natural Gas Company

3. ADDRESS OF OPERATOR

Box 4289, Farmington, New Mexico 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 790'N, 1650'W

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☒

☐

☐

☐

☐

☐

☐

☐

5. LEASE
SF 078875

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Canyon Largo Unit

8. FARM OR LEASE NAME
Canyon Largo Unit

9. WELL NO.
326

10. FIELD OR WILDCAT NAME
Devils Fork Gallup

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 33, T-25-N, R-6-W
N.M.P.M.

12. COUNTY OR PARISH Rio Arriba 13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6770' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-19-83 P.B.T.D. 6395'. Tested casing to 4000# O. K. Perforated 5980, 6010, 6022, 6032, 6042, 6061, 6082, 6112, 6113, 6144, 6157, 6167, 6181, 6200, 6225, 6252, 6268, 6286' w/1 SPZ. Fraced w/125,000# 20/40 sand and 80,000 gallons foam. Flushed w/4000 gallons foam.

12-24-83 Perforated 5056, 5085, 5093, 5106, 5118, 5131, 5152, 5166, 5192, 5608, 5649, 5694, 5708' w/80,000# 20/40 sand, 65,000 gallons foam. Flushed w/3375 gallons foam.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED D. G. Busco TITLE Drilling Clerk DATE January 5, 1983

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: