

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen a well back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐

2. NAME OF OPERATOR  
Robert L. Bayless

3. ADDRESS OF OPERATOR  
P.O. Box 1541, Farmington, NM 874999

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1990' FNL & 470' FEL

AT TOP PROD. INTERVAL: same

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(other) Spud, Cement Surf. Csg.

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)  
AUG 30 1983

BUREAU OF LAND MANAGEMENT  
FARMINGTON RESOURCE AREA

5. LEASE  
Jicarilla Contract #118

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Jicarilla

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Jicarilla 118 B

9. WELL NO.  
1

10. FIELD OR WILDCAT NAME  
Sleeper Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Section 26, T26N, R3W

12. COUNTY OR PARISH  
Rio Arriba

13. STATE  
N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
7425' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8-29-83 Spud well at 2:00 p.m. Drilled 128 ft. of 9-7/8" hole. Ran 118 ft. of 7", 23#/ft., J-55 used casing and landed at 128 ft. RKB. Rigged up Cementers Inc, cemented surface casing with 40 sacks of Class B cement w/2% CaCl. Good circulation throughout job. Circulated cement to the surface. WOC.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Swain H. McGee TITLE Engineer DATE Aug. 30, 1983

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

AUG 31 1983

\*See Instructions on Reverse Side

OPERATOR

FARMINGTON RESOURCE AREA  
BY KI