STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

rator Caulkins			ns Oil	Compar	ny	Lease _	Br	Breech "D"			No. <u>346-M</u>	
ation Well: Unit _	I	Sec2	2 Twp	26	North	Rge	. 6 We	st	Cou	nty _	Rio Arriba	
	NAME OF RESERVOIR OR POOL					TYPE OF PROD. (Oll or Gas)		METHOD OF PROD. (Flow or Art. LHI)				
pper pletien	1	1esa V	erde			Gas			Flow		Tubing	
pletion :	1					Gas			Flow		Tubing	
				PR	E-FLOW	SHUT-IN	PRESSURE	DATA				
per letion	'				ngth of lime shut-in		SI press. psig			Stabilized? (Yes or No)		
Hour, date shut-in letion			Length of time shut-in			SI press, paig		Sta		labilized? (Yes or No)		
					F	LOW TEST	NO. 1					
enced at (hour,	date)#	7:	30 AM	3-15			Zone proc	Zone producing (Upper or Low				
		APSED TIME		PRESS Upper Completion		ver Completion	PROD. 2				REMARKS	
:30 AM -16-86				407		1272		Both Zor	Both Zones Shut-in			
7:30 AM 3-17-86	1		407 1287			Both Z		ones Shut-in				
:30 AM -18-86 72 Hours		407 1292			Both Z		ones Shut-in					
7:30 AM 3-19-86	:30 AM		407 289					-in - Dakota Flowing				
7:30 AM 3-20-86	12	0 Hou	rs	407		327					Dakota Flowing	
uction rate	during	test										
		В	SOPD ba	ised on _		Bbls. i	n	Hours	s G	612v	GOR	
	· · · · · · · · · · · · · · · · · · ·			1	MCFPD;	Tested thru	ı (Orifice o	r Mete	r):			
				MI	D-TEST S	SHUT-IN P	RESSURE 1	DATA				
Hour, dal	le shul-in		,	Length of tir			SI press, psig			Stabilize	d? (Yas or No)	
Hour, dal	-Hour, date shut-in			Length of time shut-in			SI press. psig			Stabilize	d? (Yes or No)	
									MAR 26	u y		

Continue on reverse side)

OIL CON. DIV.

FLOW TEST NO. 2

TIME (hour, date) LAPSED TIME SINCE ** Upper Completion Lower Completion TEMP. REMARKS PRODUCTION TEMP. REMARKS	nmenced at (hour, date) **			Zone producing (Upper or Lower):					
Production rate during test Oil: BOPD based on Bbls. in Hours Grav GOR Gas: MCFPD: Tested thru (Orifice or Meter): Remarks:		D TIME			REMARKS				
Production rate during test Dil: BOPD based on Bbls. in Hours Grav GOR MCFPD: Tested thru (Orifice or Meter): Remarks:	(ites, date)	opper completion	Lower Completion	ICMP.	1				
Production rate during test Dil: BOPD based on Bbls. in Hours Grav GOR Gas: MCFPD: Tested thru (Orifice or Meter): Remarks:									
Production rate during test Dil:BOPD based onBbls. inHoursGravGOR Gas:MCFPD: Tested thru (Orifice or Meter): Remarks:									
Production rate during test Dil:BOPD based onBbls. inHoursGravGOR Gas:MCFPD: Tested thru (Orifice or Meter): Remarks:									
Dil:BOPD based onBbls. inHoursGravGOR Gas:MCFPD: Tested thru (Orifice or Meter): Lemarks:					'				
Dil:BOPD based onBbls. inHoursGravGOR Gas:MCFPD: Tested thru (Orifice or Meter): Lemarks:									
Dil:BOPD based onBbls. inHoursGravGOR Gas:MCFPD: Tested thru (Orifice or Meter): Lemarks:									
Dil:BOPD based onBbls. inHoursGravGOR Gas:MCFPD: Tested thru (Orifice or Meter): Remarks:									
Dil:BOPD based onBbls. inHoursGravGOR Gas:MCFPD: Tested thru (Orifice or Meter): Remarks:									
Dil:BOPD based onBbls. inHoursGravGOR Gas:MCFPD: Tested thru (Orifice or Meter): Remarks:	duction rate during t	it	بمبه	* ***					
MCFPD: Tested thru (Orifice or Meter):	l•	BOPD based on			Gray GOR				
lemarks:		•							
	s:	MCFP	D: Tested thru (O	rifice or Meter):					
hereby certify that the information herein contained is true and complete to the best of my knowledge.	narks:								
hereby certify that the information herein contained is true and complete to the best of my knowledge.									
hereby certify that the information herein contained is true and complete to the best of my knowledge.									
· · · · · · · · · · · · · · · · · · ·	ereby certify that the	sformation herein containe	d is true and comp	ete to the best of	my knowledge.				
ApprovedMAR 2 6 1986 19 Operator Caulkins Oil Company	proved	MAR 26 1986	10 Oper	earor (Caulkins Oil Company				
			•		_				
Original Signed by CHARLES GHOLSON By Official Signed by CHARLES GHOLSON	Original S	ined by CHARLES GUOLGON	Ву		harles 6 Vergine				
By Title Superintendent			Title		Superintendent /				
Title DEPLITY OIL & GAS INSPECTOR DIST #3 Date 3-24-86		_			2-2/-06				

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

Test No. 2 shall be constanted men to no less the ordering Flow in 1. Encedure for Flow Ten to the mean to the 1. 10. 1 except

- that the previously produced zone shall remain shur-in while the zone which was previously shur-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOP (oil zones only).