ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1

2001

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator	GREYSTONE E	NERGY , IN	Lease TRIBAL				Well No.	C6E	
Location of Well	Unit M	Sec	5	Twp.	26N	Rge.	3W	_API #	30-039-23458
	NAME OF RESERVOI	R OR POOL	TYPE OF PROD. (Oil or Gas)			METHOD (PROD. MEDIUM (Tbg. or Csg.)	
Upper Completion	GALLUP			GAS			SHUT-IN		TBG
Lower Completion	DAKOTA		GAS			FLOW		TBG	
	T		PRE-	FLOW SHUT-IN	I PRESSU	RE D	ATA SI press. psig		Stabilized? (Yes or No)
Upper	Hour, date shut-in 04/20/01			3 DAYS	Length of time shut-in				YES
Completion Lower	U4/2U/U1 Hour, date shut-in			S DATS Length of time shut-in			765 St press, psig		Stabilized? (Yes or No)
Completion	04/20/01			_	3 DAYS			<u> </u>	YES
				FLOV	V TEST N				····
Commenced	at (hour, date) *	04/24/01			Zone produ	cing (L	Jpper or Lower)	·	LOWER
TIME	LAPSED TIME		PRESSURE	PROD. ZONE					
(hour, date)	Since *	Upper Completic		Lower Completion	TEMP.			REMARK	<u>(S</u>
04/22		csg 765	tbg 0	tbg 650			Both Zones	Shut In	TARISTO S
04/23		765	0	700			Both Zones	Shut In	\$ 001
04/24		765	0	785			Both Zones	Shut In \approx	APR 2001 APR 2001 RECEIVED OIL ON DIV OIL OFFT. 3
04/25	1 DAY	765	0	120	,		Lower Zone	Flowing	ON DIST 3
04/26	2 DAYS	765	0	117			Lower Zone		AN GIRITA
	rate during test	1					_		·
Oil: BOPD based on				Bbls. in Hours				Grav.	GOR
Gas:		40		MCFPD: Tested the	ru (Orifice or	Meter)	METER		<u> </u>
		Š.	MID-T	EST SHUT-IN P	RESSURI	E DA	TA		
Upper Completion	Hour, date shut-in			Length of time shut-in			SI press. psig		Stabilized? (Yes or No)
Lower	Hour, date shut-in			Length of time shut-in			SI press. psig		Stabilized? (Yes or No)

(Continue on reverse side)

FLOW TEST NO. 2

	at (hour, date) **			Zone Producing (Upper or Lower):						
Time	LAPSED TIME	PRES	SURE	PROD. ZONE						
(hour, date)	SINCE **	Upper Completion	Lower Completion	TEMP.	REMARKS					
*										
		_								
	<u> </u>									
Production	rate during test			·						
Oil:	BOPD b	pased on	Bbls. in	_ Hrs	Grav GOR					
Gas:	MCFPD: Tested thru (Orifice or Meter):									
Remarks:										
I hereby certi	fy that the information	n herein contained is tr	ue and complete to th	ne best of my know	rledge.					
Approved	APR	3 0 2001, 2001	Opera	ator GREYST	ONE ENERGY, INC.					
New Mexic	co Oil Conservation	on Division		1/	1/1-					
•	DATONAL SIGNED	BY CHARLET, PARM	By	[(my)	Kelisten					
Ву			Title	PRODUCTION TECHNICIAN						
Title	MEMALA OH T	gas inspector, dis	<u>T. ≰8</u> Date	04/27/01						

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distrubed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak 'was indicated during Flow
 Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a dead-weight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-nminute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)