		,	
Form 3160-5 (November 1983) (Formerly 9-331)	UNITED STATES DEPARTMENT OF THE INTE BUREAU OF LAND MANAGEME	RIOR (Other instructions on re-	Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO. SF 079265
(Do not use this	IDRY NOTICES AND REPORTS form for proposals to drill or to deepen or plu Use "APPLICATION FOR PERMIT—" for such		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL GAS WELL NAME OF OPERATOR	OTHER		7. UNIT AGREEMENT NAME
Fl Paso Natural Gas Company 3. ADDRESS OF OPERATOR			8. FARM OR LEASE NAME Klein 9. WELL NO.
Post Office Box 4289, Farmington, NM 87499 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1190'S, 1455'E			27E 10. FIELD AND POOL, OR WILDCAT Basin Dakota
REIC EIV	/ F D		11. SEC., T., R., M., OR BLY. AND SURVEY OR AREA SEC. 35, T-26-N, R-06-V NMPM 12. COUNTY OR PARISH 13. STATE
OCT 09 19	85 63	15. BLEVATIONS (Show whether Dr. RT, CR. etc.) 6335 GL Check Appropriate Box To Indicate Nature of Notice, Report, or O	
BUREAU OF LAND MAN	ASSEMBNITHTENTION TO:		INCT DOIG
FARMINGTON RESOLD TEST WATER SHUT-OF FRACTURE TREAT SHOOT OF ACIDIZE REPAIR WELL (Other)	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS	(Norm: Report results of	REPAIRING WELL ALTERING CASING ABANDONMENT* nning Casing f multiple completion on Well
7. DESCRIBE PROPUSED OR proposed work. If nent to this work.)	COMPLETED OPERATIONS (Clearly state all pertine well is directionally drilled, give subsurface loc		tion Report and Log form.) ncluding estimated date of starting any depths for all markers and zones perti-
10-5-85	TD 7149'. Ran 166 jt production casing, 71 7136'. Stage tools @ with 290 sks. Class "	37' set @ 7149'. F 5369' and 2704'. B" 65/35 Pozmix, 6%	loat collar set @ Cemented first stage gel, 2% calcium

TD 7149'. Ran 166 jts. 4 1/2", 11.6# & 10.5# J-55 production casing, 7137' set @ 7149'. Float collar set @ 7136'. Stage tools @ 5369' and 2704'. Cemented first stage with 290 sks. Class "B" 65/35 Pozmix, 6% gel, 2% calcium chloride (470 cu.ft.) followed by 100 sks. Class "B" 65/35 Poz with 2% gel, 2% calcium chloride (124 cu.ft.), 2nd stage with 414 sks. Class "B" 65/35 Pozmix, 6% gel, 2% calcium chloride (670 cu.ft.), 3rd stage with 330 sks. Class "B" 65/35 Pozmix with 6% gel and 2% calcium chloride (535 cu.ft.). WOC 18 hours. Top of cement 1050' T.S.

Drilling Clerk	10-7-85
TITLE	DATE
	ACCEPTED FOR RECORD
TITLE	DATE
	TITLE

OCT 10 1985

*See Instructions on Reverse Side