Form 3160-5 (November 1983)	UNITED STATES	SUBMIT IN TRIPLICATES	Expires August 31, 1985	
(Formerly 9–331)	DEPARTMENT OF THE INTE		5. LEASE DESIGNATION AN	
	BUREAU OF LAND MANAGEM		Jicarilla Co	n. 103
SUN (Do not use this	DRY NOTICES AND REPORTS form for proposals to drill or to deepen or pl Use "APPLICATION FOR PERMIT—" for su	S ON WELLS lug back to a different reservoir.	6. IF INDIAN, ALLOTTEE O	ache
OIL GAS WELL	Ö 078€E		7. UNIT AGREEMENT NAME N/A	
2. NAME OF OPERATOR			8. FARM OR LEASE NAME	· · · · · · · · · · · · · · · · · · ·
Union Tex	JICARILLA H			
3. ADDRESS OF OPERATOR			9. WELL NO.	
375 US Highway 64, Farmington, NM 87401			14	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface			10. PLAND POOL OR WILDCAT	
890' FSL & 970' FEL			Basin DK, W.H. Gal 11. SBC., T., S., M., OR BLK. AND SURVEY OR ARMA	
			Sec. 18, T26	
14. PERMIT NO.	15. ELEVATIONS (Show whether	er DF, RT, GR, etc.)	12. COUNTY OR PARISH 1	3. STATE
	6687' G.L. 6699	9' K.B.	Rio Arriba	NM
16.	Check Appropriate Box To Indicat	e Nature of Notice, Report, or C	Other Data	
NOTICE OF INTENTION TO:			ENT REPORT OF:	
TEST WATER SHUT-OF	PELL OR ALTER CASING	- WATER SHUT-OFF	REPAIRING WEL	L
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASI	NG
SHOOT OR ACIDIZE	ABANDON®	SHOOTING OR ACIDIZING	ABANDONMENT*	
REPAIR WELL	CHANGE PLANS	(Other) Int. casing		X
(Other)		(Note: Report results Completion or Recompl	of multiple completion on etion Report and Log form.	Well_

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones pertinent to this work.)

Union Texas Petroleum wishes to advise that a 8-3/4" hole was drilled to 3613' KB. Run 7", 23#, N-80 casing to 3613' KB, cementing with 300 sx (861 cu.ft.) 65/35 POZ containing 12% gel and 12-1/4# gilsonite/sk, tailed by 100 sx (118 cu.ft.) Cl "B" with 2% CaCl2. Did not circulate to surface. Top of cement 1700' KB by temperature survey dated 6/19/88. Drill 6-1/4" hole with air/mist to 7725' KB. Run 4-1/2", 11.6#, N-80 production liner from 3387' to 7705' KB. Cement with 540 sx (848 cu.ft.) 50/50 POZ with 4% gel, 6-1/4# gilsonite/sk and 10# salt/sk. A cement bond log will be run during the completion to determine cement top.

Permit Coordinator (This space for Federal or State office use) APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

> *See Instructions on Reverse Side TOWN JCC