

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

(Other instructions on reverse side)

Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Amoco Production Co.

3. ADDRESS OF OPERATOR

1325 East 30th St. Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

1750' FNL x 2200' FWL

14. PERMIT NO. API No.

30 039 24310

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7265' GR

5. LEASE DESIGNATION AND SERIAL NO.

nm-69074

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Jimmons Federal Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Devilaw Mancos Est.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEHW Sec 3 T26N R2W

12. COUNTY OR PARISH

Rio Arriba

13. STATE

nm

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in and rigged up service unit on 12-6-88. Pressure tested casing to 3300 PSI. Perforated Gallup C zone interval 7312-7458' with 2 JSPE, .50" diameter, for a total of 292 holes. Graced Gallup C zone with 113,736 gal of 30 lb gel and 5,000 lb 40-70 mesh sand and 136,851 lb of 20-40 mesh Brady. Set a cast iron bridge plug at 7270' and tested to 3300 PSI. Perforated Gallup AB zone 7134-7240' with 2 JSPE, .50" diameter, for a total of 212 holes. Graced with 87,276 gal of 30 lb gel water and 5000 lb 40-70 mesh Arizona sand and 121,000 lb of 20-40 mesh Brady sand. Drilled out bridge plug. Landed 2 7/8" tubing at 7459 ft. Released rig on 1-24-89.

18. I hereby certify that the foregoing is true and correct

SIGNED

B. Shaw

TITLE

Adm Supervisor

DATE

2-9-89

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

FEB 27 1989

FARMINGTON RESOURCE AREA

*See Instructions on Reverse Side

BY Klt

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCC