

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SEE REVERSE SIDE
Other instructions on reverse side

Expires August 31, 1985
LEASE DESIGNATION AND SERIAL

SE-079160

IF INDIAN ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.

1. UNIT AGREEMENT NAME Rincon Unit	
2. FARM OR LEASE NAME Rincon Unit	
3. WELL NO. 271	
4. FIELD AND POOL OR WILDCAT Basin Fruitland Coal	
5. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 1, T.26N, R.7W	
6. COUNTY OR PARISH; STATE Rio Arriba NM	
7. NAME OF OPERATOR Union Oil Company of California	8. ADDRESS OF OPERATOR P. O. Box 671 - Midland, Texas 79702
9. LOCATION OF WELL (Report location clearly and in accordance with State requirements. See also space 17 below.) At surface 1155' FSL & 1155' FWL	
10. PERMIT NO.	11. ELEVATIONS (Show whether OF, RT, GR, etc.) 6485' GR

DECEIVE

JUL 13 1990

**OIL CON. DIV
DIST. 3**

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRAC TREAT ☐	MULTIPLE COMPLETE ☐	FRAC TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANT ☐	Other: ☐	Other: ☒

(Other) _____

NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

6-3 361' WOC. 361' 6-1/2. SD. 1" @ 316'. MUD: 8.6, 60, NC, SPUD MUD. MI RU ARAPAHOE RIG #2. SPUD 12-1/4" HOLE @ 6:00 PM 6-3-90. TD 12-1/4" HOLE @ 361' @ 1:00 AM 6-4-90. CIRC (1/4 HR) & TOH. R&C 7 JTS + 1 PC (347') 8-5/8" 20# X-42 ST&C BRD NEW SMLS CSG SET @ 360' CMT W/300 SXS CLASS "B" + 2% CACL2 + 1/4#/SX CS MIXED @ 15.6 PPG. DISPL PLUG W/21-1/2 BFW @ 4 BPM & 250 PSI. CIP & JC @ 4:30 AM 6-4-90. CIRC'D 114 SXS CMT TO SURF. WOC, INCOMP.

6/4 1864' DRLG. 1503' 11-1/2. SD & SH. 1/2" @ 865', 1/2" @ 1356'. MUD: 8.9, 31, 12. CONTINUE WOC: CUT OFF 8-5/8" CSG & WELD ON BRADEN HD & NU BOP. PRES TST BLIND RAMS, CSG & MANIFOLD TO 600 PSI FOR 30 MINS, OK. TIH & TAG CMT @ 320'. PRES TST PIPE RAMS TO 600 PSI FOR 30 MINS, OK. DRILL PLUG & CMT. DRLG NEW FORM W/7-7/8" BIT @ 5:00 PM 6-4-90. TOTAL WOC 12-1/2 HRS.

6/5 2800' CIRC FOR LOGS. 936' 18-1/2. COAL, SD & SH. 1/2" @ 1884', 3/4" @ 2382'. MUD: 8.9, 48, 9.0, 1, 7, 500. DRLG TO 2800' TD @ 1:45 AM 6-6-90. CIRC (12/ HR) & SHORT TRIP. CIRC & COND HOLE FOR LOGS, INCOMP.

6/6 MORT. 3/4" @ 2800'. MUD: 9, 41, 8, 1, 7.5 450. CONT. CIRC FOR LOGS (1-1/2 HRS). TOH-SLM & LOG & RAM MRL-SDC-GR FROM 2793'-360' W/LOGGERS TO @ 2795'. TIH & CIRC (1/2 HR). LDDP-DC'S. R&C 64 JTS & 1 PC (2786') 4-1/2" 11.6# J-55 LTC BRD NEW SMLS CSG SET @ 2799' W/DV @ 2366'. CIRC (1/2 HR) & CMT 1ST STG W/150 SX CL "H" + .9% FLOLOK + .18% THRIFTYLITE + 3% KCL + 3#/SK HISEAL MIXED @ 15.9 PPG, DISP. PLUG W/10 BFW & 33 BBLs MUD @ 4 BPM & 450 PSI. BUMP PLUG @ 1000 PSI-OK. CIP @ 6:00 PM 6/6/90. CIRC 60 SX CMT TO SURF. DROP BOMB & OPEN DV TOOL-CIRC 4 HRS. CMT 2ND STG W/500 SX PSL "B" + .8% CFL + 1/4#/SK C.S. + 3#/SK HISEAL MIXED @ 12.6 PPG, TAIL IN W/50 SX CL "B" MEET MIXED @ 15.6 PPG. DISPL CLOSING PLUG W/37 BFW @ 5 BPM & 500 PSI. CLOSE D.V. TOOL @ 2000 PSI-OK. JC & CIP @ 1045 PM 6/6/90. CIRC'D 105 SX CMT TO SURF. NU BOP-SET SLIPS & CUT OFF 4-1/2" CSG. RIG RELEASED @ 112:00 AM 6/7/90.

19. I hereby certify that the foregoing is true and correct

SIGNED Charlotte L. Secson

TITLE Drilling Clerk

DATE 6-5-90

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

ACCEPTED FOR RECORD

JUL 09 1990

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA

BY 21