

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		6. LEASE DESIGNATION AND SERIAL NO. SF-079160	
2. NAME OF OPERATOR UNION OIL COMPANY OF CALIFORNIA dba UNOCAL		7. UNIT AGREEMENT NAME RINCON UNIT	
3. ADDRESS OF OPERATOR P.O. Box 850, Bloomfield, New Mexico 87413		8. FARM OR LEASE NAME RINCON	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Rincon 7 PC - 55' FNL and 1660 FWL Rincon 192 E DK/GL - 1020' FNL and 970' FWL		9. WELL NO. 7, 192E	
14. PERMIT NO.		10. FIELD AND POOL, OR WILDCAT PC, DK, GALLUP	
15. ELEVATIONS (Show whether DF, RT, OR, etc.) 7 - 6505' GR 192 E - 6536' GL		11. SEC., T., R., M., OR BLK. AND SUBST OR AREA NW SEC 1, T26N R7W	
		12. COUNTY OR PARISH Rio Arriba	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) INSTALL CATHODIC PROTECTION

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS: (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Proposed installation of Cathodic Protection to well casing:

PROCEDURE: Drill a 6' diameter hole, 300' deep within the existing well location boundary. Six Lida St - 1.60/50 anodes will be installed below the uppermost water bearing formation in favorable locations, and back filled with coke breeze (99.5% carbon) to completely surround the anodes. A 50' plug of bentonite will be installed on top of the coke breeze.

A DC rectifier will be installed on existing well location and a buried DC positive cable will be connected to the Lida Anode from the rectifier. Negative DC cables from the rectifier will also be buried and connected to well casings to be protected. These cables will be buried 18" to 24" deep (on previously disturbed ground) in the middle of the road as shown on attached map and location schedule.

UNOCAL'S completion expectation is Jan 15, 1992.

APPROVED
DEC 18 1991
AREA MANAGER

RECEIVED
BLM
DEC-9 PM 3:15
SANTA FE, N.M.

18. I hereby certify that the foregoing is true and correct

SIGNED Mike Jabet TITLE Production Technician DATE 08/20/91

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side