

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-105
Revised 1-1-89

OIL CONSERVATION
RECEIVED
Santa Fe, New Mexico 87504-2088
JAN 24 1994
DIV

WELL API NO. 30-039-25302
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name TRIX
8. Well No. 2
9. Pool name or Wildcat GAVILAN MANCOS

WELL COMPLETION OR RECOMPLETION REPORT AND LOG					
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐					
b. Type of Completion: NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RESVR ☐ OTHER ☐					
2. Name of Operator W.M. GALLAWAY					
3. Address of Operator 3005 NORTHRIDGE, SUITE I FARMINGTON, N. MEX 87401					
4. Well Location Unit Letter M : 790' Feet From The SOUTH Line and 990' Feet From The WEST Line Section 5 Township 26N Range 2W NMPM RIO ARRIBA County					
10. Date Spudded 8-28-93	11. Date T.D. Reached 10-28-93	12. Date Compl. (Ready to Prod.) 12-17-93 1-1-94	13. Elevations (DF& RKB, RT, GR, etc.) 7105 GL	14. Elev. Casinghead 7107	
15. Total Depth 7345'	16. Plug Back T.D. 7328'	17. If Multiple Compl. How Many Zones? N/A	18. Intervals Drilled By BIG A	Rotary Tools X	Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name GAVILAN MANCOS 7000 - 7244					20. Was Directional Survey Made YES
21. Type Electric and Other Logs Run FDC/CALLIPER/CNL/GL & GR-CEMENT BOND W-VOL					22. Was Well Cored NO

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB/FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
10 3/4"	40.5 # K55	325'	14 1/4"	413 CU. FT.	NONE
7 7/8"	29.70 & 26.40	6950'	9 7/8"	289 CU. FT. 1ST STAGE	NONE
				898 CU. FT 2ND STAGE	

24. LINER RECORD					25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
5" FLUSH JT	6808	7344	73 CU. FT	NONE	2-7/8"	7268'	NONE

26. Perforation record (interval, size, and number) 7000' TO 7090' 2 J.S. PER FOOT 7118' TO 7244' 2 J.S. PER FOOT	27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.	
	DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
	7000' TO 7090'	57816 GAL 70Q 30# FOAM
	7118 TO 7244'	84200 #20-40 SAND, 67371 GAL 65Q FOAM, 75000# 20-40

28. PRODUCTION							
Date First Production 1-1-94		Production Method (Flowing, gas lift, pumping - Size and type pump) PUMPING				Well Status (Prod. or Shut-in) SHUT IN	
Date of Test 1-1-94	Hours Tested 24 HRS	Choke Size NONE	Prod'n For Test Period	Oil - Bbl. 72	Gas - MCF 130	Water - Bbl. 8	Gas - Oil Ratio 1940
Flow Tubing Press. 50	Casing Pressure 50	Calculated 24-Hour Rate	Oil - Bbl. 67	Gas - MCF 130	Water - Bbl. 8	Oil Gravity - API - (Corr.) 39.8	

29. Disposition of Gas (Sold, used for fuel, vented, etc.) TO BE SOLD	Test Witnessed By JEFF DAVIS
--	---------------------------------

30. List Attachments NONE

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature W.M. Gallaway Printed Name W.M. GALLAWAY Title OPERATOR Date 1/21/94

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____	T. Canyon _____
T. Salt _____	T. Strawn _____
B. Salt _____	T. Atoka _____
T. Yates _____	T. Miss _____
T. 7 Rivers _____	T. Devonian _____
T. Queen _____	T. Silurian _____
T. Grayburg _____	T. Montoya _____
T. San Andres _____	T. Simpson _____
T. Glorieta _____	T. McKee _____
T. Paddock _____	T. Ellenburger _____
T. Blinbry _____	T. Gr. Wash _____
T. Tubb _____	T. Delaware Sand _____
T. Drinkard _____	T. Bone Springs _____
T. Abo _____	T. _____
T. Wolfcamp _____	T. _____
T. Penn _____	T. _____
T. Cisco (Bough C) _____	T. _____

Northwestern New Mexico

T. Ojo Alamo _____	T. Penn. "B" _____
T. Kirtland-Fruitland _____	T. Penn. "C" _____
T. Pictured Cliffs _____	T. Penn. "D" _____
T. Cliff House _____	T. Leadville _____
T. Menefee _____	T. Madison _____
T. Point Lookout _____	T. Elbert _____
T. Mancos _____	T. McCracken _____
T. Gallup _____	T. Ignacio Otzie _____
Base Greenhorn _____	T. Granite _____
T. Dakota _____	T. _____
T. Morrison _____	T. _____
T. Todilto _____	T. _____
T. Entrada _____	T. _____
T. Wingate _____	T. _____
T. Chinle _____	T. _____
T. Permian _____	T. _____
T. Penn "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from 5796' to 5950'	No. 3, from _____ to _____
No. 2, from 6950 to 7244	No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from MUD DRILLING N/A to _____ feet
No. 2, from _____ to _____ feet
No. 3, from _____ to _____ feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
3282	3412	130'	OJO ALAMO				
3412	3450	38'	KIRTLAND				
3450	3510	60'	FRUITLAND COAL				
3609	3690	81'	PICTURED CLIFFS				
5440	5496	56'	CLIFFHOUSE				
5496	5796	300'	MENEFEE				
5796	5950	154'	POINT LOOKOUT				
5950	6940	990'	MANCOS				
6950	7244	294'	GALLUP				