

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

MW Petroleum Corporation

3. Address and Telephone No.

1700 Lincoln, Ste. 2000, Denver, CO 80203-4520

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1190' FSL, 790' FEL  
Sec. 26-T26N-R3W

5. Lease Designation and Serial No.

Jicarilla Apache All8

6. If Indian, Allottee or Tribe Name

Jicarilla Apache

7. If Unit or CA, Agreement Designation

---

8. Well Name and No.

Jicarilla Apache All8  
#26

9. API Well No.

39-039-25346

10. Field and Pool, or Exploratory Area

Tapacitos / PC Ext

11. County or Parish, State

Rio Arriba / NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Set prod. casing

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

MW Petroleum drilled to a total depth of 4200' on the subject well. 4 1/2", 11.6#, K-55 casing was set at 4200' with 50 sxs standard cement with 2% CaCl and 1/4#/gal Flocele. Lead cement with nitrogen 483 sxs standard with 2% CaCl and 1/4#/gal Flocele. Tailed with 180 sxs premium cement with 2% CaCl and 1/4#/gal Flocele. Cement circ to surface.

RECEIVED  
MAR 2 1994  
BUREAU OF LAND MANAGEMENT

14. I hereby certify that the foregoing is true and correct

Signed

Carolyn D. Hepp

(This space for Federal or State office use)

Title Sr. Engineering Tech.

Date 12/23/93

Approved by

Conditions of approval, if any:

Title

2/12/94  
Acting Area Manager

Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See instruction on Reverse Side